

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780019

Luminaire Tested: LER4D15D010-EC4DR600215IC9035-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780019
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D15D010-EC4DR600215IC9035-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1422.2 lumens
Efficiency: N/A
Efficacy: 90.0 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780019

CATALOG NUMBER: LER4D15D010-EC4DR600215IC9035-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P780019

CATALOG NUMBER: LER4D15D010-EC4DR600215IC9035-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	87	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	155500
5°	155118
10°	160273
15°	160442
20°	147620
25°	125559
30°	95682
35°	67652
40°	39737
45°	16039
50°	5354
55°	2572
60°	1071
65°	155
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 16039 cd/sqm



TEST NUMBER: P780019

CATALOG NUMBER: LER4D15D010-EC4DR600215IC9035-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	136.4	9.6
10°-20°	392.9	27.6
20°-30°	470.3	33.1
30°-40°	314.6	22.1
40°-50°	93.3	6.6
50°-60°	13.4	0.9
60°-70°	1.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	999.7	70.3
0°-40°	1314.2	92.4
0°-60°	1420.9	99.9
0°-90°	1422.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1422.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1423	
5°	1414	136
15°	1418	393
25°	1042	470
35°	507	315
45°	104	93
55°	14	13
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780019

CATALOG NUMBER: LER4D15D010-EC4DR600215IC9035-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	1423.2
2.5°	1421.4
5°	1414.3
7.5°	1433.5
10°	1444.6
12.5°	1442.6
15°	1418.4
17.5°	1361.3
20°	1269.6
22.5°	1159.6
25°	1041.5
27.5°	908.5
30°	758.4
32.5°	624.3
35°	507.2
37.5°	390.0
40°	278.6
42.5°	183.7
45°	103.8
47.5°	53.1
50°	31.5
52.5°	20.4
55°	13.5
57.5°	8.7
60°	4.9
62.5°	2.0
65°	0.6
67.5°	0.2
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)