

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780034

Luminaire Tested: LER4D15D010-EC4DR650215IC9027-4LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P780034
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D15D010-EC4DR650215IC9027-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1259.5 lumens
Efficiency: N/A
Efficacy: 79.7 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780034

CATALOG NUMBER: LER4D15D010-EC4DR650215IC9027-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P780034

CATALOG NUMBER: LER4D15D010-EC4DR650215IC9027-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	66791
5°	66624
10°	66570
15°	64515
20°	58734
25°	51179
30°	42567
35°	33731
40°	24344
45°	15379
50°	8014
55°	4256
60°	2231
65°	1230
70°	512
75°	564
80°	404
85°	335

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15379 cd/sqm



TEST NUMBER: P780034

CATALOG NUMBER: LER4D15D010-EC4DR650215IC9027-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	108.2	8.6
10°-20°	296.2	23.5
20°-30°	362.0	28.7
30°-40°	293.7	23.3
40°-50°	146.4	11.6
50°-60°	40.8	3.2
60°-70°	9.3	0.7
70°-80°	2.4	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	766.3	60.8
0°-40°	1060.0	84.2
0°-60°	1247.2	99.0
0°-90°	1259.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1259.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1144	
5°	1136	108
15°	1067	296
25°	794	362
35°	473	294
45°	186	146
55°	42	41
65°	9	9
75°	2	2
85°	0	1
90°	0	



TEST NUMBER: P780034

CATALOG NUMBER: LER4D15D010-EC4DR650215IC9027-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1143.6
2.5°	1142.8
5°	1136.4
7.5°	1132.7
10°	1122.5
12.5°	1101.6
15°	1067.0
17.5°	1012.9
20°	945.0
22.5°	871.7
25°	794.2
27.5°	711.4
30°	631.2
32.5°	552.0
35°	473.1
37.5°	394.2
40°	319.3
42.5°	249.1
45°	186.2
47.5°	129.7
50°	88.2
52.5°	60.8
55°	41.8
57.5°	28.2
60°	19.1
62.5°	13.3
65°	8.9
67.5°	4.5
70°	3.0
72.5°	2.9
75°	2.5
77.5°	1.7
80°	1.2
82.5°	0.9
85°	0.5
87.5°	0.3
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)