

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780196

Luminaire Tested: LER4D20D010-EC4DR3520359024-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780196
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D20D010-EC4DR3520359024-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1504.8 lumens
Efficiency: N/A
Efficacy: 65.1 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780196

CATALOG NUMBER: LER4D20D010-EC4DR3520359024-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P780196

CATALOG NUMBER: LER4D20D010-EC4DR3520359024-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	101	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	105	100	96	93	97	95	92		95	93	91		93
4	103	97	92	89	101	96	92	89	94	90	88		92	89	87		90
5	99	93	88	85	98	92	87	84	90	86	84		89	85	83		87
6	96	89	84	81	94	88	84	81	87	83	80		85	82	80		84
7	93	85	81	78	91	85	80	77	84	80	77		83	79	77		82
8	90	82	78	74	88	82	77	74	81	77	74		80	76	74		79
9	87	79	75	72	86	79	75	72	78	74	71		77	74	71		77
10	84	77	72	69	83	76	72	69	76	72	69		75	71	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	452394
5°	441762
10°	398142
15°	309019
20°	175270
25°	68186
30°	25435
35°	13952
40°	9114
45°	5547
50°	3536
55°	2495
60°	1836
65°	982
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5547 cd/sqm



TEST NUMBER: P780196

CATALOG NUMBER: LER4D20D010-EC4DR3520359024-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	370.4	24.6
10°-20°	723.3	48.1
20°-30°	295.0	19.6
30°-40°	70.6	4.7
40°-50°	29.4	2.0
50°-60°	12.2	0.8
60°-70°	3.8	0.3
70°-80°	0.1	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1388.6	92.3
0°-40°	1459.2	97.0
0°-60°	1500.8	99.7
0°-90°	1504.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1504.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4140	
5°	4028	370
15°	2732	723
25°	566	295
35°	105	71
45°	36	29
55°	13	12
65°	4	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780196

CATALOG NUMBER: LER4D20D010-EC4DR3520359024-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	4140.5
2.5°	4115.7
5°	4027.8
7.5°	3852.6
10°	3588.6
12.5°	3216.9
15°	2731.9
17.5°	2138.8
20°	1507.4
22.5°	961.2
25°	565.6
27.5°	319.7
30°	201.6
32.5°	141.6
35°	104.6
37.5°	80.8
40°	63.9
42.5°	49.2
45°	35.9
47.5°	26.9
50°	20.8
52.5°	16.5
55°	13.1
57.5°	10.6
60°	8.4
62.5°	6.1
65°	3.8
67.5°	1.4
70°	0.2
72.5°	0.2
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.2
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)