

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780203

Luminaire Tested: LER4D20D010-EC4DR3520359027-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780203
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D20D010-EC4DR3520359027-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1706.8 lumens
Efficiency: N/A
Efficacy: 73.9 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780203

CATALOG NUMBER: LER4D20D010-EC4DR3520359027-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P780203

CATALOG NUMBER: LER4D20D010-EC4DR3520359027-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	101	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	105	100	96	94	97	95	92		95	93	91		93
4	103	97	92	89	101	96	92	89	94	90	88		92	89	87		90
5	99	93	88	85	98	92	87	84	90	86	84		89	85	83		87
6	96	89	84	81	94	88	84	81	87	83	80		85	82	80		84
7	93	85	81	78	91	85	80	77	84	80	77		83	79	77		82
8	90	82	78	74	88	82	77	74	81	77	74		80	76	74		79
9	87	79	75	72	86	79	75	72	78	74	71		77	74	71		77
10	84	77	72	69	83	76	72	69	76	72	69		75	71	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	513121
5°	501064
10°	451596
15°	350510
20°	198803
25°	77337
30°	28854
35°	15819
40°	10341
45°	6289
50°	3995
55°	2819
60°	2076
65°	1138
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6289 cd/sqm



TEST NUMBER: P780203

CATALOG NUMBER: LER4D20D010-EC4DR3520359027-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	420.2	24.6
10°-20°	820.4	48.1
20°-30°	334.6	19.6
30°-40°	80.1	4.7
40°-50°	33.4	2.0
50°-60°	13.8	0.8
60°-70°	4.3	0.3
70°-80°	0.1	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1575.1	92.3
0°-40°	1655.2	97.0
0°-60°	1702.3	99.7
0°-90°	1706.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1706.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4696	
5°	4568	420
15°	3099	820
25°	642	335
35°	119	80
45°	41	33
55°	15	14
65°	4	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780203

CATALOG NUMBER: LER4D20D010-EC4DR3520359027-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	4696.3
2.5°	4668.1
5°	4568.5
7.5°	4369.7
10°	4070.4
12.5°	3648.8
15°	3098.7
17.5°	2425.9
20°	1709.8
22.5°	1090.3
25°	641.5
27.5°	362.7
30°	228.7
32.5°	160.6
35°	118.6
37.5°	91.7
40°	72.5
42.5°	55.8
45°	40.7
47.5°	30.5
50°	23.5
52.5°	18.7
55°	14.8
57.5°	12.0
60°	9.5
62.5°	6.9
65°	4.4
67.5°	1.5
70°	0.2
72.5°	0.2
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.2
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)