

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780258

Luminaire Tested: LER4D20D010-EC4DR4520359035-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780258
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D20D010-EC4DR4520359035-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2203.6 lumens
Efficiency: N/A
Efficacy: 95.4 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780258

CATALOG NUMBER: LER4D20D010-EC4DR4520359035-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P780258

CATALOG NUMBER: LER4D20D010-EC4DR4520359035-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	425560
5°	413443
10°	395557
15°	362013
20°	287206
25°	179303
30°	98824
35°	44376
40°	17486
45°	8236
50°	3910
55°	2038
60°	1005
65°	233
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8236 cd/sqm



TEST NUMBER: P780258

CATALOG NUMBER: LER4D20D010-EC4DR4520359035-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	354.2	16.1
10°-20°	871.7	39.6
20°-30°	690.3	31.3
30°-40°	229.9	10.4
40°-50°	45.6	2.1
50°-60°	10.3	0.5
60°-70°	1.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1916.2	87.0
0°-40°	2146.1	97.4
0°-60°	2202.1	99.9
0°-90°	2203.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2203.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3895	
5°	3770	354
15°	3200	872
25°	1487	690
35°	333	230
45°	53	46
55°	11	10
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780258

CATALOG NUMBER: LER4D20D010-EC4DR4520359035-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	3894.9
2.5°	3869.5
5°	3769.6
7.5°	3687.2
10°	3565.3
12.5°	3402.9
15°	3200.4
17.5°	2895.9
20°	2470.1
22.5°	1962.8
25°	1487.3
27.5°	1089.1
30°	783.3
32.5°	532.7
35°	332.7
37.5°	197.3
40°	122.6
42.5°	80.6
45°	53.3
47.5°	34.3
50°	23.0
52.5°	15.3
55°	10.7
57.5°	7.0
60°	4.6
62.5°	2.5
65°	0.9
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°







(END OF REPORT)