

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780361

Luminaire Tested: LER4D20D010-EC4DR6520359050-4LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P780361
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D20D010-EC4DR6520359050-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1823.4 lumens
Efficiency: N/A
Efficacy: 78.9 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780361

CATALOG NUMBER: LER4D20D010-EC4DR6520359050-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P780361

CATALOG NUMBER: LER4D20D010-EC4DR6520359050-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93		
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85		
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78		
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72		
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66		
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61		
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56		
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52		
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49		
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	96693
5°	96447
10°	96364
15°	93393
20°	85024
25°	74095
30°	61626
35°	48825
40°	35246
45°	22268
50°	11603
55°	6171
60°	3236
65°	1783
70°	751
75°	835
80°	572
85°	469

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 22268 cd/sqm



TEST NUMBER: P780361

CATALOG NUMBER: LER4D20D010-EC4DR6520359050-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.6	8.6
10°-20°	428.7	23.5
20°-30°	524.1	28.7
30°-40°	425.2	23.3
40°-50°	211.9	11.6
50°-60°	59.1	3.2
60°-70°	13.4	0.7
70°-80°	3.5	0.2
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1109.4	60.8
0°-40°	1534.6	84.2
0°-60°	1805.6	99.0
0°-90°	1823.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1823.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1656	
5°	1645	157
15°	1545	429
25°	1150	524
35°	685	425
45°	270	212
55°	61	59
65°	13	13
75°	4	3
85°	1	1
90°	0	



TEST NUMBER: P780361

CATALOG NUMBER: LER4D20D010-EC4DR6520359050-4LBS1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1655.6
2.5°	1654.4
5°	1645.1
7.5°	1639.8
10°	1624.9
12.5°	1594.8
15°	1544.6
17.5°	1466.3
20°	1368.0
22.5°	1261.9
25°	1149.8
27.5°	1029.8
30°	913.8
32.5°	799.2
35°	684.8
37.5°	570.8
40°	462.3
42.5°	360.6
45°	269.6
47.5°	187.8
50°	127.7
52.5°	88.1
55°	60.6
57.5°	40.9
60°	27.7
62.5°	19.2
65°	12.9
67.5°	6.6
70°	4.4
72.5°	4.1
75°	3.7
77.5°	2.4
80°	1.7
82.5°	1.2
85°	0.7
87.5°	0.5
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)