

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780446

Luminaire Tested: LER4D25D010-EC4DR2520359030-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780446
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR2520359030-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2353.2 lumens
Efficiency: N/A
Efficacy: 93.8 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780446

CATALOG NUMBER: LER4D25D010-EC4DR2520359030-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P780446

CATALOG NUMBER: LER4D25D010-EC4DR2520359030-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94
4	103	97	93	90	102	96	93	90	94	91	89		93	90	88		91
5	100	93	89	86	98	93	89	86	91	87	85		89	86	84		88
6	97	90	85	82	95	89	85	82	88	84	81		87	83	81		85
7	93	87	82	79	92	86	82	79	85	81	78		84	80	78		83
8	91	84	79	76	90	83	79	76	82	78	76		81	78	75		80
9	88	81	76	73	87	80	76	73	80	76	73		79	75	73		78
10	85	78	74	71	85	78	74	71	77	73	71		76	73	71		76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	975152
5°	908233
10°	647871
15°	381571
20°	237418
25°	130297
30°	59587
35°	22568
40°	10227
45°	6150
50°	2550
55°	1657
60°	1158
65°	776
70°	128
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6150 cd/sqm



TEST NUMBER: P780446

CATALOG NUMBER: LER4D25D010-EC4DR2520359030-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	711.7	30.2
10°-20°	963.9	41.0
20°-30°	510.1	21.7
30°-40°	125.9	5.4
40°-50°	30.7	1.3
50°-60°	8.1	0.3
60°-70°	2.7	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2185.7	92.9
0°-40°	2311.6	98.2
0°-60°	2350.4	99.9
0°-90°	2353.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2353.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8925	
5°	8281	712
15°	3373	964
25°	1081	510
35°	169	126
45°	40	31
55°	9	8
65°	3	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780446

CATALOG NUMBER: LER4D25D010-EC4DR2520359030-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	8925.0
2.5°	8778.4
5°	8280.9
7.5°	7281.5
10°	5839.5
12.5°	4414.3
15°	3373.3
17.5°	2629.0
20°	2041.9
22.5°	1531.3
25°	1080.8
27.5°	724.8
30°	472.3
32.5°	287.3
35°	169.2
37.5°	103.5
40°	71.7
42.5°	54.8
45°	39.8
47.5°	24.0
50°	15.0
52.5°	10.9
55°	8.7
57.5°	6.8
60°	5.3
62.5°	4.1
65°	3.0
67.5°	1.1
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)