

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780489

Luminaire Tested: LER4D25D010-EC4DR3520359027-4LBS1H

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780489
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR3520359027-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2320.2 lumens
Efficiency: N/A
Efficacy: 92.4 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780489

CATALOG NUMBER: LER4D25D010-EC4DR3520359027-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P780489

CATALOG NUMBER: LER4D25D010-EC4DR3520359027-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	101	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	105	100	96	93	97	95	92		95	93	91		93
4	103	97	92	89	101	96	92	89	94	90	88		92	89	87		90
5	99	93	88	85	98	92	87	84	90	86	84		89	85	83		87
6	96	89	84	81	94	88	84	81	87	83	80		85	82	80		84
7	93	85	81	78	91	85	80	77	84	80	77		83	79	77		82
8	90	82	78	74	88	82	77	74	81	77	74		80	76	74		79
9	87	79	75	72	86	79	75	72	78	74	71		77	74	71		77
10	84	77	72	69	83	76	72	69	76	72	69		75	71	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	697521
5°	681134
10°	613888
15°	476475
20°	270241
25°	105137
30°	39224
35°	21501
40°	14049
45°	8545
50°	5439
55°	3848
60°	2819
65°	1525
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8545 cd/sqm



TEST NUMBER: P780489

CATALOG NUMBER: LER4D25D010-EC4DR3520359027-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	571.2	24.6
10°-20°	1115.2	48.1
20°-30°	454.8	19.6
30°-40°	108.8	4.7
40°-50°	45.3	2.0
50°-60°	18.8	0.8
60°-70°	5.9	0.3
70°-80°	0.1	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2141.1	92.3
0°-40°	2250.0	97.0
0°-60°	2314.1	99.7
0°-90°	2320.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2320.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6384	
5°	6210	571
15°	4212	1115
25°	872	455
35°	161	109
45°	55	45
55°	20	19
65°	6	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780489

CATALOG NUMBER: LER4D25D010-EC4DR3520359027-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	6384.0
2.5°	6345.7
5°	6210.3
7.5°	5940.1
10°	5533.2
12.5°	4960.1
15°	4212.3
17.5°	3297.7
20°	2324.2
22.5°	1482.1
25°	872.1
27.5°	493.0
30°	310.9
32.5°	218.3
35°	161.2
37.5°	124.6
40°	98.5
42.5°	75.9
45°	55.3
47.5°	41.4
50°	32.0
52.5°	25.4
55°	20.2
57.5°	16.4
60°	12.9
62.5°	9.4
65°	5.9
67.5°	2.1
70°	0.3
72.5°	0.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)