

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780500

Luminaire Tested: LER4D25D010-EC4DR3520359040-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780500
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR3520359040-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2418.0 lumens
Efficiency: N/A
Efficacy: 96.3 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780500

CATALOG NUMBER: LER4D25D010-EC4DR3520359040-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P780500

CATALOG NUMBER: LER4D25D010-EC4DR3520359040-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	101	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	105	100	96	93	97	95	92		95	93	91		93
4	103	97	92	89	101	96	92	89	94	90	88		92	89	87		90
5	99	93	88	85	98	92	87	84	90	86	84		89	85	83		87
6	96	89	84	81	94	88	84	81	87	83	80		85	82	80		84
7	93	85	81	78	91	85	80	77	84	80	77		83	79	77		82
8	90	82	78	74	88	82	77	74	81	77	74		80	76	74		79
9	87	79	75	72	86	79	75	72	78	74	71		77	74	71		77
10	84	77	72	69	83	76	72	69	76	72	69		75	71	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	726934
5°	709859
10°	639772
15°	496564
20°	281648
25°	109573
30°	40877
35°	22408
40°	14648
45°	8916
50°	5677
55°	4000
60°	2928
65°	1603
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8916 cd/sqm



TEST NUMBER: P780500

CATALOG NUMBER: LER4D25D010-EC4DR3520359040-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	595.2	24.6
10°-20°	1162.2	48.1
20°-30°	474.0	19.6
30°-40°	113.4	4.7
40°-50°	47.3	2.0
50°-60°	19.6	0.8
60°-70°	6.1	0.3
70°-80°	0.1	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2231.4	92.3
0°-40°	2344.9	97.0
0°-60°	2411.7	99.7
0°-90°	2418.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2418.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6653	
5°	6472	595
15°	4390	1162
25°	909	474
35°	168	113
45°	58	47
55°	21	20
65°	6	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780500

CATALOG NUMBER: LER4D25D010-EC4DR3520359040-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	6653.2
2.5°	6613.3
5°	6472.2
7.5°	6190.6
10°	5766.5
12.5°	5169.3
15°	4389.9
17.5°	3436.7
20°	2422.3
22.5°	1544.6
25°	908.9
27.5°	513.8
30°	324.0
32.5°	227.5
35°	168.0
37.5°	129.9
40°	102.7
42.5°	79.1
45°	57.7
47.5°	43.2
50°	33.4
52.5°	26.5
55°	21.0
57.5°	17.1
60°	13.4
62.5°	9.8
65°	6.2
67.5°	2.2
70°	0.3
72.5°	0.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)