

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780504

Luminaire Tested: LER4D25D010-EC4DR3520359050-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780504
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR3520359050-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2389.5 lumens
Efficiency: N/A
Efficacy: 95.2 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780504

CATALOG NUMBER: LER4D25D010-EC4DR3520359050-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P780504

CATALOG NUMBER: LER4D25D010-EC4DR3520359050-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96			
2	110	106	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92			
3	106	101	97	94	105	100	96	93	97	95	92	95	93	91	93	91	89	88			
4	103	97	92	89	101	96	92	89	94	90	88	92	89	87	90	88	86	84			
5	99	93	88	85	98	92	87	84	90	86	84	89	85	83	87	84	82	81			
6	96	89	84	81	94	88	84	81	87	83	80	85	82	80	84	81	79	78			
7	93	85	81	78	91	85	80	77	84	80	77	83	79	77	82	79	76	75			
8	90	82	78	74	88	82	77	74	81	77	74	80	76	74	79	76	73	72			
9	87	79	75	72	86	79	75	72	78	74	71	77	74	71	77	73	71	70			
10	84	77	72	69	83	76	72	69	76	72	69	75	71	69	74	71	69	68			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	718368
5°	701479
10°	632227
15°	490716
20°	278322
25°	108283
30°	40398
35°	22142
40°	14477
45°	8808
50°	5609
55°	3962
60°	2906
65°	1577
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8808 cd/sqm



TEST NUMBER: P780504

CATALOG NUMBER: LER4D25D010-EC4DR3520359050-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	588.2	24.6
10°-20°	1148.5	48.1
20°-30°	468.4	19.6
30°-40°	112.1	4.7
40°-50°	46.7	2.0
50°-60°	19.3	0.8
60°-70°	6.1	0.3
70°-80°	0.1	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2205.1	92.3
0°-40°	2317.2	97.0
0°-60°	2383.2	99.7
0°-90°	2389.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2389.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6575	
5°	6396	588
15°	4338	1148
25°	898	468
35°	166	112
45°	57	47
55°	21	19
65°	6	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780504

CATALOG NUMBER: LER4D25D010-EC4DR3520359050-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	6574.8
2.5°	6535.4
5°	6395.8
7.5°	6117.6
10°	5698.5
12.5°	5108.3
15°	4338.2
17.5°	3396.2
20°	2393.7
22.5°	1526.3
25°	898.2
27.5°	507.7
30°	320.2
32.5°	224.8
35°	166.0
37.5°	128.3
40°	101.5
42.5°	78.2
45°	57.0
47.5°	42.7
50°	33.0
52.5°	26.2
55°	20.8
57.5°	16.8
60°	13.3
62.5°	9.7
65°	6.1
67.5°	2.2
70°	0.3
72.5°	0.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)