

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780544

Luminaire Tested: LER4D25D010-EC4DR4520359035-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780544
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR4520359035-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2539.7 lumens
Efficiency: N/A
Efficacy: 101.2 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780544

CATALOG NUMBER: LER4D25D010-EC4DR4520359035-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P780544

CATALOG NUMBER: LER4D25D010-EC4DR4520359035-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	490482
5°	476518
10°	455900
15°	417248
20°	331017
25°	206657
30°	113913
35°	51152
40°	20139
45°	9487
50°	4504
55°	2362
60°	1158
65°	259
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9487 cd/sqm



TEST NUMBER: P780544

CATALOG NUMBER: LER4D25D010-EC4DR4520359035-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	408.2	16.1
10°-20°	1004.7	39.6
20°-30°	795.6	31.3
30°-40°	265.0	10.4
40°-50°	52.6	2.1
50°-60°	11.9	0.5
60°-70°	1.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2208.5	87.0
0°-40°	2473.5	97.4
0°-60°	2538.0	99.9
0°-90°	2539.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2539.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4489	
5°	4345	408
15°	3689	1005
25°	1714	796
35°	384	265
45°	61	53
55°	12	12
65°	1	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780544

CATALOG NUMBER: LER4D25D010-EC4DR4520359035-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	4489.1
2.5°	4459.8
5°	4344.7
7.5°	4249.7
10°	4109.2
12.5°	3922.1
15°	3688.7
17.5°	3337.7
20°	2846.9
22.5°	2262.2
25°	1714.2
27.5°	1255.2
30°	902.9
32.5°	614.0
35°	383.5
37.5°	227.4
40°	141.2
42.5°	92.9
45°	61.4
47.5°	39.5
50°	26.5
52.5°	17.6
55°	12.4
57.5°	8.1
60°	5.3
62.5°	2.8
65°	1.0
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)