

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780592

Luminaire Tested: LER4D25D010-EC4DR5520359035-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780592
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR5520359035-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2541.1 lumens
Efficiency: N/A
Efficacy: 101.2 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780592

CATALOG NUMBER: LER4D25D010-EC4DR5520359035-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P780592

CATALOG NUMBER: LER4D25D010-EC4DR5520359035-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	311339
5°	298972
10°	297846
15°	289292
20°	259393
25°	214373
30°	161931
35°	117417
40°	75137
45°	34318
50°	11219
55°	4838
60°	2076
65°	259
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 34318 cd/sqm



TEST NUMBER: P780592

CATALOG NUMBER: LER4D25D010-EC4DR5520359035-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	259.4	10.2
10°-20°	707.9	27.9
20°-30°	806.7	31.7
30°-40°	549.2	21.6
40°-50°	189.2	7.4
50°-60°	26.1	1.0
60°-70°	2.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1774.0	69.8
0°-40°	2323.2	91.4
0°-60°	2538.6	99.9
0°-90°	2541.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2541.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2850	
5°	2726	259
15°	2558	708
25°	1778	807
35°	880	549
45°	222	189
55°	25	26
65°	1	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780592

CATALOG NUMBER: LER4D25D010-EC4DR5520359035-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	2849.5
2.5°	2784.2
5°	2725.9
7.5°	2697.3
10°	2684.6
12.5°	2642.3
15°	2557.5
17.5°	2423.0
20°	2230.9
22.5°	2009.2
25°	1778.2
27.5°	1537.7
30°	1283.5
32.5°	1068.2
35°	880.3
37.5°	701.6
40°	526.8
42.5°	365.1
45°	222.1
47.5°	119.7
50°	66.0
52.5°	39.2
55°	25.4
57.5°	16.2
60°	9.5
62.5°	4.2
65°	1.0
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)