

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780633

Luminaire Tested: LER4D25D010-EC4DR6520359027-4LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P780633
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR6520359027-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2128.6 lumens
Efficiency: N/A
Efficacy: 84.8 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780633

CATALOG NUMBER: LER4D25D010-EC4DR6520359027-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P780633

CATALOG NUMBER: LER4D25D010-EC4DR6520359027-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	112871
5°	112587
10°	112495
15°	109023
20°	99251
25°	86493
30°	71937
35°	56996
40°	41140
45°	25993
50°	13547
55°	7199
60°	3785
65°	2087
70°	871
75°	948
80°	673
85°	603

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25993 cd/sqm



TEST NUMBER: P780633

CATALOG NUMBER: LER4D25D010-EC4DR6520359027-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	182.8	8.6
10°-20°	500.5	23.5
20°-30°	611.8	28.7
30°-40°	496.4	23.3
40°-50°	247.4	11.6
50°-60°	69.0	3.2
60°-70°	15.7	0.7
70°-80°	4.1	0.2
80°-90°	1.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1295.0	60.8
0°-40°	1791.4	84.2
0°-60°	2107.7	99.0
0°-90°	2128.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2128.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1933	
5°	1920	183
15°	1803	500
25°	1342	612
35°	799	496
45°	315	247
55°	71	69
65°	15	16
75°	4	4
85°	1	1
90°	0	



TEST NUMBER: P780633

CATALOG NUMBER: LER4D25D010-EC4DR6520359027-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1932.6
2.5°	1931.2
5°	1920.4
7.5°	1914.2
10°	1896.9
12.5°	1861.6
15°	1803.1
17.5°	1711.7
20°	1596.9
22.5°	1473.1
25°	1342.2
27.5°	1202.2
30°	1066.7
32.5°	932.9
35°	799.4
37.5°	666.3
40°	539.6
42.5°	420.9
45°	314.7
47.5°	219.3
50°	149.1
52.5°	102.8
55°	70.7
57.5°	47.7
60°	32.4
62.5°	22.5
65°	15.1
67.5°	7.7
70°	5.1
72.5°	4.8
75°	4.2
77.5°	2.9
80°	2.0
82.5°	1.4
85°	0.9
87.5°	0.6
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)