

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780661

Luminaire Tested: LER4D25D010-EC4DR7020359030-4LBS1H

Issue Date: 1/31/2024

Test Information

Test Method: LM-79-2019
Report Number: P780661
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/31/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D25D010-EC4DR7020359030-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2531.8 lumens
Efficiency: N/A
Efficacy: 100.9 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P780661

CATALOG NUMBER: LER4D25D010-EC4DR7020359030-4LBS1H

Luminous Intensity Polar Plot



TEST NUMBER: P780661

CATALOG NUMBER: LER4D25D010-EC4DR7020359030-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	76	93	86	80	76	83	78	75		81	77	74		79
5	89	80	74	69	88	79	73	69	78	72	68		76	71	68		74
6	84	75	68	63	83	74	68	63	72	67	63		71	66	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	58	54	74	64	58	54	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	53	50		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	218336
5°	217788
10°	217322
15°	217260
20°	215140
25°	202088
30°	180161
35°	143653
40°	95377
45°	57017
50°	29559
55°	15544
60°	5507
65°	78
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 57017 cd/sqm



TEST NUMBER: P780661

CATALOG NUMBER: LER4D25D010-EC4DR7020359030-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	188.8	7.5
10°-20°	541.6	21.4
20°-30°	764.0	30.2
30°-40°	659.6	26.1
40°-50°	295.3	11.7
50°-60°	77.3	3.1
60°-70°	5.0	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1494.5	59.0
0°-40°	2154.1	85.1
0°-60°	2526.8	99.8
0°-90°	2531.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2531.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1998	
5°	1986	189
15°	1921	542
25°	1676	764
35°	1077	660
45°	369	295
55°	82	77
65°	0	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780661

CATALOG NUMBER: LER4D25D010-EC4DR7020359030-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1998.3
2.5°	1996.2
5°	1985.7
7.5°	1977.1
10°	1958.8
12.5°	1942.2
15°	1920.7
17.5°	1895.9
20°	1850.3
22.5°	1775.2
25°	1676.3
27.5°	1561.7
30°	1428.0
32.5°	1264.6
35°	1077.0
37.5°	870.0
40°	668.7
42.5°	508.1
45°	369.0
47.5°	254.4
50°	173.9
52.5°	120.0
55°	81.6
57.5°	49.2
60°	25.2
62.5°	7.9
65°	0.3
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)