

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P780979

Luminaire Tested: LER4D35BD010-EC4DR2520359035-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P780979
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D35BD010-EC4DR2520359035-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2885.7 lumens
Efficiency: N/A
Efficacy: 93.7 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P780979

CATALOG NUMBER: LER4D35BD010-EC4DR2520359035-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P780979

CATALOG NUMBER: LER4D35BD010-EC4DR2520359035-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94
4	103	97	93	90	102	96	93	90	94	91	89		93	90	88		91
5	100	93	89	86	98	93	89	86	91	87	85		89	86	84		88
6	97	90	85	82	95	89	85	82	88	84	81		87	83	81		85
7	93	87	82	79	92	86	82	79	85	81	78		84	80	78		83
8	91	84	79	76	90	83	79	76	82	78	76		81	78	75		80
9	88	81	76	73	87	80	76	73	80	76	73		79	75	73		78
10	85	78	74	71	85	78	74	71	77	73	71		76	73	71		76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1195815
5°	1113748
10°	794464
15°	467912
20°	291136
25°	159773
30°	73074
35°	27677
40°	12537
45°	7540
50°	3128
55°	2019
60°	1399
65°	957
70°	160
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7540 cd/sqm



TEST NUMBER: P780979

CATALOG NUMBER: LER4D35BD010-EC4DR2520359035-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	872.7	30.2
10°-20°	1182.0	41.0
20°-30°	625.5	21.7
30°-40°	154.4	5.4
40°-50°	37.7	1.3
50°-60°	9.9	0.3
60°-70°	3.3	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2680.2	92.9
0°-40°	2834.7	98.2
0°-60°	2882.3	99.9
0°-90°	2885.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2885.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10945	
5°	10155	873
15°	4137	1182
25°	1325	626
35°	208	154
45°	49	38
55°	11	10
65°	4	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P780979

CATALOG NUMBER: LER4D35BD010-EC4DR2520359035-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	10944.6
2.5°	10764.7
5°	10154.7
7.5°	8929.2
10°	7160.8
12.5°	5413.2
15°	4136.6
17.5°	3223.9
20°	2503.9
22.5°	1877.8
25°	1325.3
27.5°	888.8
30°	579.2
32.5°	352.4
35°	207.5
37.5°	127.0
40°	87.9
42.5°	67.2
45°	48.8
47.5°	29.4
50°	18.4
52.5°	13.3
55°	10.6
57.5°	8.3
60°	6.4
62.5°	5.1
65°	3.7
67.5°	1.4
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)