

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781121

Luminaire Tested: LER4D35BD010-EC4DR5520359035-4LBS1H

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781121
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D35BD010-EC4DR5520359035-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3475.9 lumens
Efficiency: N/A
Efficacy: 112.9 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781121

CATALOG NUMBER: LER4D35BD010-EC4DR5520359035-4LBS1H

Luminous Intensity Polar Plot



TEST NUMBER: P781121

CATALOG NUMBER: LER4D35BD010-EC4DR5520359035-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	425866
5°	408957
10°	407417
15°	395710
20°	354807
25°	293240
30°	221505
35°	160606
40°	102779
45°	46943
50°	15349
55°	6629
60°	2841
65°	362
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 46943 cd/sqm



TEST NUMBER: P781121

CATALOG NUMBER: LER4D35BD010-EC4DR5520359035-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	354.8	10.2
10°-20°	968.3	27.9
20°-30°	1103.5	31.7
30°-40°	751.2	21.6
40°-50°	258.9	7.4
50°-60°	35.8	1.0
60°-70°	3.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2426.6	69.8
0°-40°	3177.9	91.4
0°-60°	3472.5	99.9
0°-90°	3475.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3475.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3898	
5°	3729	355
15°	3498	968
25°	2432	1104
35°	1204	751
45°	304	259
55°	35	36
65°	1	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781121

CATALOG NUMBER: LER4D35BD010-EC4DR5520359035-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	3897.7
2.5°	3808.4
5°	3728.7
7.5°	3689.6
10°	3672.2
12.5°	3614.2
15°	3498.3
17.5°	3314.3
20°	3051.5
22.5°	2748.2
25°	2432.4
27.5°	2103.4
30°	1755.7
32.5°	1461.1
35°	1204.1
37.5°	959.7
40°	720.6
42.5°	499.4
45°	303.8
47.5°	163.7
50°	90.3
52.5°	53.6
55°	34.8
57.5°	22.2
60°	13.0
62.5°	5.8
65°	1.4
67.5°	0.5
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)