

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781134

Luminaire Tested: LER4D35BD010-EC4DR6020359024-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781134
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D35BD010-EC4DR6020359024-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3035.1 lumens
Efficiency: N/A
Efficacy: 98.5 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781134

CATALOG NUMBER: LER4D35BD010-EC4DR6020359024-4LBS1LI

Luminous Intensity Polar Plot



TEST NUMBER: P781134

CATALOG NUMBER: LER4D35BD010-EC4DR6020359024-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89	87		
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81		
4	97	90	84	80	95	88	83	79	86	82	78	84	81	78	82	79	77	75		
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70		
6	87	79	73	68	86	78	72	68	76	71	68	75	70	67	74	70	67	65		
7	83	74	68	63	82	73	67	63	72	67	63	71	66	63	69	65	62	61		
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	61	58	57		
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53		
10	72	62	56	52	71	61	56	52	61	55	52	60	55	52	59	55	52	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	331869
5°	331052
10°	342047
15°	342399
20°	315053
25°	267972
30°	204183
35°	144387
40°	84793
45°	34210
50°	11423
55°	5505
60°	2251
65°	336
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 34210 cd/sqm



TEST NUMBER: P781134

CATALOG NUMBER: LER4D35BD010-EC4DR6020359024-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	291.2	9.6
10°-20°	838.6	27.6
20°-30°	1003.7	33.1
30°-40°	671.3	22.1
40°-50°	199.0	6.6
50°-60°	28.6	0.9
60°-70°	2.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2133.5	70.3
0°-40°	2804.8	92.4
0°-60°	3032.4	99.9
0°-90°	3035.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3035.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3037	
5°	3018	291
15°	3027	839
25°	2223	1004
35°	1082	671
45°	221	199
55°	29	29
65°	1	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781134

CATALOG NUMBER: LER4D35BD010-EC4DR6020359024-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	3037.4
2.5°	3033.5
5°	3018.4
7.5°	3059.3
10°	3083.0
12.5°	3078.7
15°	3027.0
17.5°	2905.1
20°	2709.6
22.5°	2474.8
25°	2222.8
27.5°	1938.9
30°	1618.4
32.5°	1332.4
35°	1082.5
37.5°	832.3
40°	594.5
42.5°	392.0
45°	221.4
47.5°	113.3
50°	67.2
52.5°	43.5
55°	28.9
57.5°	18.5
60°	10.3
62.5°	4.3
65°	1.3
67.5°	0.4
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)