

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781175

Luminaire Tested: LER4D35BD010-EC4DR6520359040-4LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P781175
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D35BD010-EC4DR6520359040-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2962.7 lumens
Efficiency: N/A
Efficacy: 96.2 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781175

CATALOG NUMBER: LER4D35BD010-EC4DR6520359040-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P781175

CATALOG NUMBER: LER4D35BD010-EC4DR6520359040-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	157106
5°	156710
10°	156577
15°	151753
20°	138152
25°	120390
30°	100127
35°	79340
40°	57264
45°	36177
50°	18854
55°	10019
60°	5268
65°	2902
70°	1212
75°	1331
80°	942
85°	804

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 36177 cd/sqm



TEST NUMBER: P781175

CATALOG NUMBER: LER4D35BD010-EC4DR6520359040-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	254.4	8.6
10°-20°	696.6	23.5
20°-30°	851.5	28.7
30°-40°	690.9	23.3
40°-50°	344.3	11.6
50°-60°	96.0	3.2
60°-70°	21.8	0.7
70°-80°	5.7	0.2
80°-90°	1.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1802.5	60.8
0°-40°	2493.4	84.2
0°-60°	2933.7	99.0
0°-90°	2962.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2962.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2690	
5°	2673	254
15°	2510	697
25°	1868	852
35°	1113	691
45°	438	344
55°	98	96
65°	21	22
75°	6	6
85°	1	1
90°	0	



TEST NUMBER: P781175

CATALOG NUMBER: LER4D35BD010-EC4DR6520359040-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2690.0
2.5°	2688.0
5°	2673.0
7.5°	2664.3
10°	2640.2
12.5°	2591.2
15°	2509.8
17.5°	2382.5
20°	2222.8
22.5°	2050.4
25°	1868.2
27.5°	1673.3
30°	1484.7
32.5°	1298.6
35°	1112.8
37.5°	927.4
40°	751.1
42.5°	585.8
45°	438.0
47.5°	305.2
50°	207.5
52.5°	143.1
55°	98.4
57.5°	66.4
60°	45.1
62.5°	31.2
65°	21.0
67.5°	10.7
70°	7.1
72.5°	6.7
75°	5.9
77.5°	4.0
80°	2.8
82.5°	2.0
85°	1.2
87.5°	0.8
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)