

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781308

Luminaire Tested: LER4D40BD010-EC4DR4540509030-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781308
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D40BD010-EC4DR4540509030-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3798.3 lumens
Efficiency: N/A
Efficacy: 107.9 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781308

CATALOG NUMBER: LER4D40BD010-EC4DR4540509030-4LBS1B

Luminous Intensity Polar Plot



TEST NUMBER: P781308

CATALOG NUMBER: LER4D40BD010-EC4DR4540509030-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	733533
5°	712645
10°	681809
15°	623999
20°	495043
25°	309069
30°	170346
35°	76495
40°	30123
45°	14200
50°	6731
55°	3524
60°	1726
65°	414
70°	160
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14200 cd/sqm



TEST NUMBER: P781308

CATALOG NUMBER: LER4D40BD010-EC4DR4540509030-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	610.5	16.1
10°-20°	1502.5	39.6
20°-30°	1189.9	31.3
30°-40°	396.3	10.4
40°-50°	78.6	2.1
50°-60°	17.8	0.5
60°-70°	2.6	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3302.9	87.0
0°-40°	3699.2	97.4
0°-60°	3795.7	99.9
0°-90°	3798.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3798.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6714	
5°	6498	611
15°	5516	1503
25°	2564	1190
35°	574	396
45°	92	79
55°	18	18
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781308

CATALOG NUMBER: LER4D40BD010-EC4DR4540509030-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	6713.6
2.5°	6669.7
5°	6497.6
7.5°	6355.5
10°	6145.4
12.5°	5865.5
15°	5516.5
17.5°	4991.6
20°	4257.6
22.5°	3383.2
25°	2563.7
27.5°	1877.2
30°	1350.2
32.5°	918.3
35°	573.5
37.5°	340.1
40°	211.2
42.5°	138.9
45°	91.9
47.5°	59.1
50°	39.6
52.5°	26.4
55°	18.5
57.5°	12.1
60°	7.9
62.5°	4.2
65°	1.6
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)