

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781316

Luminaire Tested: LER4D40BD010-EC4DR4540509040-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781316
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D40BD010-EC4DR4540509040-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4017.8 lumens
Efficiency: N/A
Efficacy: 114.1 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781316

CATALOG NUMBER: LER4D40BD010-EC4DR4540509040-4LBS1B

Luminous Intensity Polar Plot



TEST NUMBER: P781316

CATALOG NUMBER: LER4D40BD010-EC4DR4540509040-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	775915
5°	753818
10°	721206
15°	660049
20°	523646
25°	326923
30°	180187
35°	80910
40°	31863
45°	15019
50°	7122
55°	3715
60°	1836
65°	440
70°	192
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15019 cd/sqm



TEST NUMBER: P781316

CATALOG NUMBER: LER4D40BD010-EC4DR4540509040-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	645.8	16.1
10°-20°	1589.4	39.6
20°-30°	1258.6	31.3
30°-40°	419.1	10.4
40°-50°	83.2	2.1
50°-60°	18.9	0.5
60°-70°	2.8	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3493.8	87.0
0°-40°	3912.9	97.4
0°-60°	4014.9	99.9
0°-90°	4017.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4017.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7102	
5°	6873	646
15°	5835	1589
25°	2712	1259
35°	607	419
45°	97	83
55°	20	19
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781316

CATALOG NUMBER: LER4D40BD010-EC4DR4540509040-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	7101.5
2.5°	7055.1
5°	6873.0
7.5°	6722.8
10°	6500.5
12.5°	6204.4
15°	5835.2
17.5°	5280.0
20°	4503.6
22.5°	3578.7
25°	2711.8
27.5°	1985.7
30°	1428.2
32.5°	971.3
35°	606.6
37.5°	359.7
40°	223.4
42.5°	146.9
45°	97.2
47.5°	62.6
50°	41.9
52.5°	27.9
55°	19.5
57.5°	12.8
60°	8.4
62.5°	4.5
65°	1.7
67.5°	0.6
70°	0.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)