

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781372

Luminaire Tested: LER4D40BD010-EC4DR6040509024-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781372
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D40BD010-EC4DR6040509024-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3188.7 lumens
Efficiency: N/A
Efficacy: 90.6 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781372

CATALOG NUMBER: LER4D40BD010-EC4DR6040509024-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P781372

CATALOG NUMBER: LER4D40BD010-EC4DR6040509024-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	87	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	348651
5°	347800
10°	359355
15°	359717
20°	330982
25°	281522
30°	214516
35°	151696
40°	89072
45°	35941
50°	12001
55°	5772
60°	2382
65°	362
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 35941 cd/sqm



TEST NUMBER: P781372

CATALOG NUMBER: LER4D40BD010-EC4DR6040509024-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	305.9	9.6
10°-20°	881.0	27.6
20°-30°	1054.5	33.1
30°-40°	705.3	22.1
40°-50°	209.1	6.6
50°-60°	30.1	0.9
60°-70°	2.9	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2241.4	70.3
0°-40°	2946.6	92.4
0°-60°	3185.8	99.9
0°-90°	3188.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3188.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3191	
5°	3171	306
15°	3180	881
25°	2335	1054
35°	1137	705
45°	233	209
55°	30	30
65°	1	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781372

CATALOG NUMBER: LER4D40BD010-EC4DR6040509024-4LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	3191.0
2.5°	3186.9
5°	3171.1
7.5°	3214.1
10°	3239.0
12.5°	3234.4
15°	3180.1
17.5°	3052.1
20°	2846.6
22.5°	2600.0
25°	2335.2
27.5°	2037.0
30°	1700.3
32.5°	1399.8
35°	1137.3
37.5°	874.3
40°	624.5
42.5°	411.8
45°	232.6
47.5°	119.0
50°	70.6
52.5°	45.7
55°	30.3
57.5°	19.5
60°	10.9
62.5°	4.5
65°	1.4
67.5°	0.5
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)