

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781448

Luminaire Tested: LER4D45BD010-EC4DR2540509027-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781448
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D45BD010-EC4DR2540509027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3522.1 lumens
Efficiency: N/A
Efficacy: 91.0 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781448

CATALOG NUMBER: LER4D45BD010-EC4DR2540509027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P781448

CATALOG NUMBER: LER4D45BD010-EC4DR2540509027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96			
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92			
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89			
4	103	97	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85			
5	100	93	89	86	98	93	89	86	91	87	85	89	86	84	88	85	83	82			
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79			
7	93	87	82	79	92	86	82	79	85	81	78	84	80	78	83	80	78	77			
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74			
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72			
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1459527
5°	1359372
10°	969670
15°	571107
20°	355353
25°	195011
30°	89185
35°	33773
40°	15290
45°	9194
50°	3825
55°	2457
60°	1726
65°	1163
70°	192
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9194 cd/sqm



TEST NUMBER: P781448

CATALOG NUMBER: LER4D45BD010-EC4DR2540509027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1065.2	30.2
10°-20°	1442.7	41.0
20°-30°	763.5	21.7
30°-40°	188.5	5.4
40°-50°	46.0	1.3
50°-60°	12.1	0.3
60°-70°	4.1	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3271.4	92.9
0°-40°	3459.8	98.2
0°-60°	3517.9	99.9
0°-90°	3522.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3522.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13358	
5°	12394	###
15°	5049	1443
25°	1618	763
35°	253	188
45°	60	46
55°	13	12
65°	4	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781448

CATALOG NUMBER: LER4D45BD010-EC4DR2540509027-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	13358.2
2.5°	13138.7
5°	12394.2
7.5°	10898.4
10°	8740.0
12.5°	6607.0
15°	5048.9
17.5°	3934.9
20°	3056.2
22.5°	2292.0
25°	1617.6
27.5°	1084.8
30°	706.9
32.5°	430.1
35°	253.2
37.5°	155.0
40°	107.2
42.5°	82.0
45°	59.5
47.5°	35.9
50°	22.5
52.5°	16.3
55°	12.9
57.5°	10.1
60°	7.9
62.5°	6.2
65°	4.5
67.5°	1.7
70°	0.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)