

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P781859

Luminaire Tested: LER4D50D010-EC4DR6040509027-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P781859
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4D50D010-EC4DR6040509027-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4712.6 lumens
Efficiency: N/A
Efficacy: 100.3 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P781859

CATALOG NUMBER: LER4D50D010-EC4DR6040509027-4LBS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P781859

CATALOG NUMBER: LER4D50D010-EC4DR6040509027-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89	87		
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81		
4	97	90	84	80	95	88	83	79	86	82	78	84	81	78	82	79	77	75		
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70		
6	87	79	73	68	86	78	72	68	76	71	68	75	70	67	74	70	67	65		
7	83	74	68	63	82	73	67	63	72	67	63	71	66	63	69	65	62	61		
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	61	58	57		
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53		
10	72	62	56	52	71	61	56	52	61	55	52	60	55	52	59	55	52	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	515285
5°	514017
10°	531100
15°	531641
20°	489172
25°	416075
30°	317036
35°	224190
40°	131647
45°	53123
50°	17729
55°	8534
60°	3518
65°	517
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 53123 cd/sqm



TEST NUMBER: P781859

CATALOG NUMBER: LER4D50D010-EC4DR6040509027-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	452.1	9.6
10°-20°	1302.1	27.6
20°-30°	1558.4	33.1
30°-40°	1042.3	22.1
40°-50°	309.0	6.6
50°-60°	44.4	0.9
60°-70°	4.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3312.6	70.3
0°-40°	4354.9	92.4
0°-60°	4708.4	99.9
0°-90°	4712.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4712.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4716	
5°	4687	452
15°	4700	1302
25°	3451	1558
35°	1681	1042
45°	344	309
55°	45	44
65°	2	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P781859

CATALOG NUMBER: LER4D50D010-EC4DR6040509027-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	4716.1
2.5°	4710.0
5°	4686.6
7.5°	4750.2
10°	4787.0
12.5°	4780.3
15°	4700.0
17.5°	4510.7
20°	4207.1
22.5°	3842.5
25°	3451.3
27.5°	3010.5
30°	2512.9
32.5°	2068.8
35°	1680.8
37.5°	1292.2
40°	923.0
42.5°	608.7
45°	343.8
47.5°	175.9
50°	104.3
52.5°	67.6
55°	44.8
57.5°	28.8
60°	16.1
62.5°	6.7
65°	2.0
67.5°	0.7
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)