

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P784395

Luminaire Tested: LER4DD35BD010-EC4DR2520359050-4LBDP1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P784395
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4DD35BD010-EC4DR2520359050-4LBDP1MW
Description: 4 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2693.7 lumens
Efficiency: N/A
Efficacy: 87.5 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 30.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P784395

CATALOG NUMBER: LER4DD35BD010-EC4DR2520359050-4LBDP1MW

Luminous Intensity Polar Plot



TEST NUMBER: P784395

CATALOG NUMBER: LER4DD35BD010-EC4DR2520359050-4LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94
4	103	97	93	90	102	96	93	90	94	91	89		93	90	88		91
5	100	93	89	86	98	93	89	86	91	87	85		89	86	84		88
6	97	90	85	82	95	89	85	82	88	84	81		87	83	81		85
7	93	87	82	79	92	86	82	79	85	81	78		84	80	78		83
8	91	84	79	76	90	83	79	76	82	78	76		81	78	75		80
9	88	81	76	73	87	80	76	73	80	76	73		79	75	73		78
10	85	78	74	71	85	78	74	71	77	73	71		76	73	71		76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1116295
5°	1039694
10°	741643
15°	436794
20°	271776
25°	149152
30°	68217
35°	25836
40°	11696
45°	7031
50°	2924
55°	1886
60°	1311
65°	879
70°	128
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7031 cd/sqm



TEST NUMBER: P784395

CATALOG NUMBER: LER4DD35BD010-EC4DR2520359050-4LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	814.7	30.2
10°-20°	1103.4	41.0
20°-30°	583.9	21.7
30°-40°	144.2	5.4
40°-50°	35.2	1.3
50°-60°	9.3	0.3
60°-70°	3.1	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2502.0	92.9
0°-40°	2646.2	98.2
0°-60°	2690.6	99.9
0°-90°	2693.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2693.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10217	
5°	9480	815
15°	3862	1103
25°	1237	584
35°	194	144
45°	46	35
55°	10	9
65°	3	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P784395

CATALOG NUMBER: LER4DD35BD010-EC4DR2520359050-4LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	10216.8
2.5°	10048.9
5°	9479.5
7.5°	8335.4
10°	6684.7
12.5°	5053.2
15°	3861.5
17.5°	3009.5
20°	2337.4
22.5°	1753.0
25°	1237.2
27.5°	829.7
30°	540.7
32.5°	329.0
35°	193.7
37.5°	118.5
40°	82.0
42.5°	62.7
45°	45.5
47.5°	27.5
50°	17.2
52.5°	12.5
55°	9.9
57.5°	7.7
60°	6.0
62.5°	4.7
65°	3.4
67.5°	1.3
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)