

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P784836

Luminaire Tested: LER4DD40BD010-EC4DR7040509030-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P784836
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4DD40BD010-EC4DR7040509030-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2209.4 lumens
Efficiency: N/A
Efficacy: 62.8 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P784836

CATALOG NUMBER: LER4DD40BD010-EC4DR7040509030-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P784836

CATALOG NUMBER: LER4DD40BD010-EC4DR7040509030-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		95
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	86	80	75	92	85	79	74	82	77	73		80	76	73		78
5	89	80	74	69	87	79	73	69	77	72	68		75	71	67		74
6	85	75	68	64	83	74	68	64	73	67	63		71	66	63		70
7	80	70	64	59	79	70	64	59	68	63	59		67	62	59		66
8	77	66	60	56	75	66	60	56	65	59	55		64	59	55		63
9	73	63	57	52	72	62	56	52	61	56	52		60	55	52		60
10	70	59	53	49	69	59	53	49	58	53	49		57	52	49		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	271404
5°	263337
10°	255997
15°	252642
20°	235906
25°	177229
30°	125280
35°	44376
40°	23334
45°	24862
50°	25735
55°	26211
60°	26376
65°	25827
70°	24375
75°	22585
80°	20072
85°	16297

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 57.5°

Luminance: 26395 cd/sqm



TEST NUMBER: P784836

CATALOG NUMBER: LER4DD40BD010-EC4DR7040509030-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	226.5	10.3
10°-20°	621.2	28.1
20°-30°	684.1	31.0
30°-40°	261.4	11.8
40°-50°	123.4	5.6
50°-60°	122.7	5.6
60°-70°	98.2	4.4
70°-80°	56.5	2.6
80°-90°	15.4	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1531.8	69.3
0°-40°	1793.2	81.2
0°-60°	2039.3	92.3
0°-90°	2209.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2209.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2484	
5°	2401	226
15°	2234	621
25°	1470	684
35°	333	261
45°	161	123
55°	138	123
65°	100	98
75°	54	56
85°	13	15
90°	0	



TEST NUMBER: P784836

CATALOG NUMBER: LER4DD40BD010-EC4DR7040509030-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	2484.0
2.5°	2458.0
5°	2401.0
7.5°	2353.4
10°	2307.4
12.5°	2268.5
15°	2233.5
17.5°	2148.9
20°	2028.9
22.5°	1770.2
25°	1470.1
27.5°	1279.7
30°	993.0
32.5°	641.4
35°	332.7
37.5°	179.7
40°	163.6
42.5°	162.4
45°	160.9
47.5°	157.3
50°	151.4
52.5°	144.7
55°	137.6
57.5°	129.8
60°	120.7
62.5°	110.5
65°	99.9
67.5°	88.1
70°	76.3
72.5°	64.5
75°	53.5
77.5°	42.1
80°	31.9
82.5°	22.4
85°	13.0
87.5°	5.1
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°







(END OF REPORT)