

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P784896

Luminaire Tested: LER4DD45BD010-EC4DR3040509050-4LBDP1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P784896
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4DD45BD010-EC4DR3040509050-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3451.4 lumens
Efficiency: N/A
Efficacy: 89.2 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P784896

CATALOG NUMBER: LER4DD45BD010-EC4DR3040509050-4LBDP1B

Luminous Intensity Polar Plot



TEST NUMBER: P784896

CATALOG NUMBER: LER4DD45BD010-EC4DR3040509050-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96		
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92		
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89		
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85		
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82		
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79		
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77		
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74		
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72		
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69		

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	849479	849479	849479
5°	825093	824125	825132
10°	714651	709614	714487
15°	466277	463773	461443
20°	231856	240555	231546
25°	116795	131701	114404
30°	46764	50954	40745
35°	21688	20772	17408
40°	9363	10402	8823
45°	6603	8194	6668
50°	2274	5966	2405
55°	1308	2469	1388
60°	919	1087	919
65°	598	598	598
70°	358	246	358
75°	0	148	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°

Vertical Angle: 45°

Luminance: 8194 cd/sqm



TEST NUMBER: P784896

CATALOG NUMBER: LER4DD45BD010-EC4DR3040509050-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	975.9	28.3
10°-20°	1571.7	45.5
20°-30°	679.2	19.7
30°-40°	154.8	4.5
40°-50°	53.2	1.5
50°-60°	13.0	0.4
60°-70°	3.4	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3226.8	93.5
0°-40°	3381.6	98.0
0°-60°	3447.7	99.9
0°-90°	3451.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3451.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	11098	11098	11098	11098	11098	
5°	10738	10728	10726	10748	10739	977
15°	5884	5813	5852	5833	5823	1576
25°	1383	1435	1559	1399	1355	662
35°	232	237	222	221	186	157
45°	61	76	76	76	62	43
55°	10	10	18	11	10	10
65°	3	3	3	3	3	3
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	

TEST NUMBER: P784896

CATALOG NUMBER: LER4DD45BD010-EC4DR3040509050-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	11098.0	11098.0	11098.0	11098.0	11098.0
2.5°	11024.4	11016.8	11021.2	11026.6	11028.8
5°	10738.4	10728.0	10725.8	10748.2	10738.9
7.5°	10161.4	10146.6	10124.3	10175.0	10222.4
10°	9194.7	9178.4	9129.9	9153.9	9192.6
12.5°	7767.7	7714.9	7713.8	7790.1	7779.7
15°	5884.1	5813.3	5852.5	5833.4	5823.1
17.5°	3956.9	3929.6	3981.9	3966.1	3898.0
20°	2846.4	2853.5	2953.2	2903.1	2842.6
22.5°	2077.1	2102.7	2220.9	2091.8	2044.4
25°	1382.9	1435.2	1559.4	1398.7	1354.6
27.5°	850.5	874.5	1000.4	839.7	815.7
30°	529.1	517.1	576.5	494.7	461.0
32.5°	347.1	331.8	350.9	314.9	287.7
35°	232.1	237.0	222.3	220.7	186.3
37.5°	144.9	166.7	147.1	156.9	119.9
40°	93.7	121.0	104.1	115.0	88.3
42.5°	76.8	93.2	85.5	91.0	78.5
45°	61.0	75.7	75.7	75.7	61.6
47.5°	33.8	50.7	64.8	51.8	36.0
50°	19.1	25.6	50.1	26.7	20.2
52.5°	13.1	14.7	34.3	15.3	13.6
55°	9.8	10.4	18.5	10.9	10.4
57.5°	7.6	8.2	9.8	8.2	7.6
60°	6.0	6.0	7.1	6.5	6.0
62.5°	4.4	4.4	4.9	4.4	4.4
65°	3.3	3.3	3.3	3.3	3.3
67.5°	1.6	2.2	2.2	2.2	2.2
70°	1.6	1.1	1.1	1.1	1.6
72.5°	1.1	0.5	0.5	0.5	0.5
75°	0.0	0.0	0.5	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180° - - 45°-225° - - - 90°-270°







(END OF REPORT)