

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P785172

Luminaire Tested: LER4DD50D010-EC4DR4040509030-4LBDP1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P785172
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4DD50D010-EC4DR4040509030-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4502.4 lumens
Efficiency: N/A
Efficacy: 95.8 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P785172

CATALOG NUMBER: LER4DD50D010-EC4DR4040509030-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P785172

CATALOG NUMBER: LER4DD50D010-EC4DR4040509030-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	100	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	104	100	96	93	97	94	92		95	93	90		93
4	102	97	92	89	101	95	91	88	93	90	87		92	89	86		90
5	99	92	88	84	97	91	87	84	90	86	83		88	85	83		87
6	95	88	84	80	94	88	83	80	86	82	80		85	82	79		84
7	92	85	80	77	91	84	80	77	83	79	76		82	79	76		81
8	89	82	77	74	88	81	77	74	80	76	73		79	76	73		78
9	86	79	74	71	85	78	74	71	77	73	71		76	73	70		76
10	83	76	71	68	82	75	71	68	75	71	68		74	70	68		73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1145370
5°	1139797
10°	1077355
15°	915893
20°	624246
25°	260461
30°	81893
35°	38067
40°	21052
45°	9657
50°	4691
55°	2572
60°	1333
65°	465
70°	192
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9657 cd/sqm

TEST NUMBER: P785172

CATALOG NUMBER: LER4DD50D010-EC4DR4040509030-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	970.4	21.6
10°-20°	2173.9	48.3
20°-30°	1088.2	24.2
30°-40°	199.5	4.4
40°-50°	55.0	1.2
50°-60°	12.9	0.3
60°-70°	2.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4232.4	94.0
0°-40°	4431.9	98.4
0°-60°	4499.9	99.9
0°-90°	4502.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4502.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10483	
5°	10392	970
15°	8097	2174
25°	2160	1088
35°	285	199
45°	62	55
55°	14	13
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P785172

CATALOG NUMBER: LER4DD50D010-EC4DR4040509030-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	10482.9
2.5°	10467.6
5°	10392.2
7.5°	10152.2
10°	9710.6
12.5°	9022.3
15°	8097.0
17.5°	6893.7
20°	5368.8
22.5°	3660.2
25°	2160.5
27.5°	1142.1
30°	649.1
32.5°	419.5
35°	285.4
37.5°	203.9
40°	147.6
42.5°	101.0
45°	62.5
47.5°	39.8
50°	27.6
52.5°	19.6
55°	13.5
57.5°	8.6
60°	6.1
62.5°	3.7
65°	1.8
67.5°	1.2
70°	0.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)