

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P785306

Luminaire Tested: LER4DD50D010-EC4DR6540509050-4LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P785306
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LER4DD50D010-EC4DR6540509050-4LBDP1LI
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4743.5 lumens
Efficiency: N/A
Efficacy: 100.9 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P785306

CATALOG NUMBER: LER4DD50D010-EC4DR6540509050-4LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P785306

CATALOG NUMBER: LER4DD50D010-EC4DR6540509050-4LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	89	84	79	95	88	83	79	86	82	78		84	80	77		82
5	92	83	78	73	90	83	77	73	81	76	72		79	75	72		77
6	87	78	72	68	86	77	72	68	76	71	67		74	70	67		73
7	83	73	67	63	81	73	67	63	71	66	62		70	66	62		69
8	79	69	63	59	77	68	63	59	67	62	58		66	62	58		65
9	75	65	59	55	74	65	59	55	64	58	55		63	58	55		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	510281
5°	510705
10°	528681
15°	529559
20°	487544
25°	415412
30°	318020
35°	224670
40°	132617
45°	53834
50°	19514
55°	10877
60°	6228
65°	3438
70°	3610
75°	2786
80°	2894
85°	2507

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 53834 cd/sqm



TEST NUMBER: P785306

CATALOG NUMBER: LER4DD50D010-EC4DR6540509050-4LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	449.7	9.5
10°-20°	1297.2	27.3
20°-30°	1556.4	32.8
30°-40°	1046.0	22.1
40°-50°	313.1	6.6
50°-60°	55.2	1.2
60°-70°	15.7	0.3
70°-80°	7.7	0.2
80°-90°	2.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3303.3	69.6
0°-40°	4349.3	91.7
0°-60°	4717.6	99.5
0°-90°	4743.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4743.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4670	
5°	4656	450
15°	4682	1297
25°	3446	1556
35°	1684	1046
45°	348	313
55°	57	55
65°	13	16
75°	7	8
85°	2	2
90°	0	



TEST NUMBER: P785306

CATALOG NUMBER: LER4DD50D010-EC4DR6540509050-4LBDP1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	4670.3
2.5°	4690.2
5°	4656.4
7.5°	4726.7
10°	4765.2
12.5°	4755.9
15°	4681.6
17.5°	4499.8
20°	4193.1
22.5°	3832.1
25°	3445.8
27.5°	3009.8
30°	2520.7
32.5°	2077.3
35°	1684.4
37.5°	1296.2
40°	929.8
42.5°	607.3
45°	348.4
47.5°	184.5
50°	114.8
52.5°	79.6
55°	57.1
57.5°	41.1
60°	28.5
62.5°	18.6
65°	13.3
67.5°	11.9
70°	11.3
72.5°	8.6
75°	6.6
77.5°	6.0
80°	4.6
82.5°	3.3
85°	2.0
87.5°	1.3
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)