

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191428

Luminaire Tested: **LDA4A10927D010TE LAR25NF 4LAL1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14  
Report Number: P1191428  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26145)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA4A10927D010TE LAR25NF 4LAL1  
Description: PORTFOLIO 4" Lensed Adjustable, Self-flange Trim Ring, 25° Narrow Flood Optic, at 0° tilt  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 922.5 lumens  
Efficiency: N/A  
Efficacy: 74.4 lumens/watt  
Spacing Criteria (0/90/45): 0.41 / 0.41 / 0.45  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 12.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P1191428

CATALOG NUMBER: LDA4A10927D010TE LAR25NF 4LAL1

### Luminous Intensity Polar Plot





TEST NUMBER: P1191428

CATALOG NUMBER: LDA4A10927D010TE LAR25NF 4LAL1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |  |     |     |     |  |  |     |     |     |  |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|--|-----|-----|-----|--|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     |  | 20  |     |     |  |  | 20  |     |     |  |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     |  | 50  |     |     |  |  | 30  |     |     |  |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |  | 50  | 30  | 10  |  |  | 50  | 30  | 10  |  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |  |     |     |     |  |  |     |     |     |  |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 |  | 111 | 111 | 111 |  |  | 106 | 106 | 106 |  |  | 102 |
| 1   | 115 | 113 | 111 | 109 | 113 | 111 | 109 | 108 |  | 107 | 106 | 104 |  |  | 103 | 102 | 101 |  |  | 100 |
| 2   | 111 | 108 | 105 | 103 | 109 | 106 | 104 | 101 |  | 103 | 101 | 99  |  |  | 100 | 99  | 97  |  |  | 98  |
| 3   | 108 | 103 | 100 | 97  | 106 | 102 | 99  | 96  |  | 100 | 97  | 95  |  |  | 97  | 95  | 93  |  |  | 95  |
| 4   | 105 | 100 | 96  | 93  | 103 | 98  | 95  | 92  |  | 97  | 94  | 91  |  |  | 95  | 92  | 90  |  |  | 93  |
| 5   | 102 | 96  | 92  | 89  | 100 | 95  | 91  | 89  |  | 94  | 90  | 88  |  |  | 92  | 89  | 87  |  |  | 91  |
| 6   | 99  | 93  | 89  | 86  | 98  | 92  | 88  | 86  |  | 91  | 87  | 85  |  |  | 90  | 87  | 84  |  |  | 88  |
| 7   | 96  | 90  | 86  | 83  | 95  | 89  | 85  | 83  |  | 88  | 85  | 82  |  |  | 87  | 84  | 82  |  |  | 86  |
| 8   | 94  | 87  | 83  | 80  | 93  | 87  | 83  | 80  |  | 86  | 82  | 80  |  |  | 85  | 82  | 80  |  |  | 84  |
| 9   | 91  | 85  | 81  | 78  | 90  | 84  | 80  | 78  |  | 83  | 80  | 78  |  |  | 83  | 80  | 77  |  |  | 82  |
| 10  | 89  | 82  | 78  | 76  | 88  | 82  | 78  | 76  |  | 81  | 78  | 76  |  |  | 81  | 78  | 75  |  |  | 80  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 536442 |
| 5°  | 432703 |
| 10° | 325233 |
| 15° | 216165 |
| 20° | 115943 |
| 25° | 29329  |
| 30° | 6965   |
| 35° | 2289   |
| 40° | 950    |
| 45° | 419    |
| 50° | 192    |
| 55° | 108    |
| 60° | 123    |
| 65° | 146    |
| 70° | 0      |
| 75° | 0      |
| 80° | 0      |
| 85° | 0      |



TEST NUMBER: P1191428

CATALOG NUMBER: LDA4A10927D010TE LAR25NF 4LAL1

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 307.2  | 33.3      |
| 10°-20°   | 457.7  | 49.6      |
| 20°-30°   | 143.0  | 15.5      |
| 30°-40°   | 11.7   | 1.3       |
| 40°-50°   | 2.0    | 0.2       |
| 50°-60°   | 0.5    | 0.1       |
| 60°-70°   | 0.3    | 0.0       |
| 70°-80°   | 0.0    | 0.0       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 907.9  | 98.4      |
| 0°-40°    | 919.6  | 99.7      |
| 0°-60°    | 922.2  | 100.0     |
| 0°-90°    | 922.5  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 922.5  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 4349 |      |
| 5°  | 3495 | 307  |
| 15° | 1693 | 458  |
| 25° | 216  | 143  |
| 35° | 15   | 12   |
| 45° | 2    | 2    |
| 55° | 0    | 1    |
| 65° | 0    | 0    |
| 75° | 0    | 0    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P1191428

CATALOG NUMBER: LDA4A10927D010TE LAR25NF 4LAL1

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 4349.1 |
| 1°    | 4263.1 |
| 2°    | 4055.4 |
| 3°    | 3837.3 |
| 4°    | 3657.4 |
| 5°    | 3494.7 |
| 6°    | 3342.7 |
| 7°    | 3178.9 |
| 8°    | 2993.2 |
| 9°    | 2800.5 |
| 10°   | 2596.7 |
| 11°   | 2401.7 |
| 12°   | 2218.4 |
| 13°   | 2041.3 |
| 14°   | 1866.4 |
| 15°   | 1692.8 |
| 17.5° | 1262.2 |
| 20°   | 883.3  |
| 22.5° | 572.4  |
| 25°   | 215.5  |
| 27.5° | 86.0   |
| 30°   | 48.9   |
| 32.5° | 25.9   |
| 35°   | 15.2   |
| 37.5° | 9.3    |
| 40°   | 5.9    |
| 42.5° | 3.4    |
| 45°   | 2.4    |
| 47.5° | 1.5    |
| 50°   | 1.0    |
| 52.5° | 0.5    |
| 55°   | 0.5    |
| 57.5° | 0.5    |
| 60°   | 0.5    |
| 62.5° | 0.5    |
| 65°   | 0.5    |
| 67.5° | 0.0    |
| 70°   | 0.0    |
| 72.5° | 0.0    |
| 75°   | 0.0    |
| 77.5° | 0.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |

Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P1191428  
CATALOG NUMBER: LDA4A10927D010TE LAR25NF 4LAL1

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

## Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



|       |     |
|-------|-----|
| 85°   | 0.0 |
| 87.5° | 0.0 |

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)