

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191516

Luminaire Tested: **LDA4A15927D010TE LAR25NF 4LA1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191516
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25629)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A15927D010TE LAR25NF 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 25° Narrow Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1345.3 lumens
Efficiency: N/A
Efficacy: 65.9 lumens/watt
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.45
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191516

CATALOG NUMBER: LDA4A15927D010TE LAR25NF 4LA1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191516

CATALOG NUMBER: LDA4A15927D010TE LAR25NF 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	113	111	110	113	111	109	108		107	106	105			103	102	101			100
2	112	108	105	103	109	106	104	102		103	101	99			100	99	97			98
3	108	104	100	97	106	102	99	97		100	97	95			98	96	94			96
4	105	100	96	93	103	99	95	93		97	94	92			95	93	91			93
5	102	96	92	89	101	95	92	89		94	91	88			92	90	88			91
6	99	93	89	86	98	93	89	86		91	88	85			90	87	85			89
7	97	90	86	83	95	90	86	83		89	85	83			88	85	83			87
8	94	88	84	81	93	87	83	81		86	83	81			85	82	80			85
9	92	85	81	79	91	85	81	79		84	81	78			83	80	78			83
10	89	83	79	76	89	83	79	76		82	79	76			81	78	76			81

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	749596
5°	657083
10°	490097
15°	311772
20°	165337
25°	37304
30°	8959
35°	2560
40°	886
45°	262
50°	154
55°	172
60°	197
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191516
 CATALOG NUMBER: LDA4A15927D010TE LAR25NF 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	464.2	34.5
10°-20°	667.0	49.6
20°-30°	197.2	14.7
30°-40°	14.0	1.0
40°-50°	1.6	0.1
50°-60°	0.7	0.1
60°-70°	0.5	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1328.5	98.8
0°-40°	1342.5	99.8
0°-60°	1344.8	100.0
0°-90°	1345.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1345.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6077	
5°	5307	464
15°	2442	667
25°	274	197
35°	17	14
45°	2	2
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191516
CATALOG NUMBER: LDA4A15927D010TE LAR25NF 4LA1

CANDELA DISTRIBUTION (FULL):

	0°
0°	6077.2
2.5°	5758.0
5°	5306.9
7.5°	4720.5
10°	3913.0
12.5°	3153.6
15°	2441.5
17.5°	1779.0
20°	1259.6
22.5°	797.5
25°	274.1
27.5°	119.6
30°	62.9
32.5°	31.8
35°	17.0
37.5°	10.1
40°	5.5
42.5°	3.1
45°	1.5
47.5°	0.8
50°	0.8
52.5°	0.8
55°	0.8
57.5°	0.8
60°	0.8
62.5°	0.8
65°	0.0
67.5°	0.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)