

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191540

Luminaire Tested: **LDA4A15930D010TE LAR35FL 4LA1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191540
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25630)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A15930D010TE LAR35FL 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: ELECTRONIC DRIVER


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1607.3 lumens
Efficiency: N/A
Efficacy: 78.8 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191540
CATALOG NUMBER: LDA4A15930D010TE LAR35FL 4LA1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191540

CATALOG NUMBER: LDA4A15930D010TE LAR35FL 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100
1	115	113	111	109	113	111	109	107	107	105	104	103	102	101	100	99	98	97	97	97
2	111	108	104	102	109	106	103	101	103	101	99	100	98	97	97	96	95	93	93	93
3	108	103	99	96	106	102	98	96	99	96	94	97	95	93	95	93	91	90	90	90
4	104	99	95	92	103	98	94	91	96	93	90	94	91	89	92	90	88	87	87	87
5	101	95	91	88	100	94	90	87	93	89	87	91	88	86	90	87	85	84	84	84
6	98	92	87	84	97	91	87	84	90	86	84	88	85	83	87	85	83	81	81	81
7	95	88	84	81	94	88	84	81	87	83	81	86	83	80	85	82	80	79	79	79
8	92	86	81	78	91	85	81	78	84	81	78	83	80	78	82	80	77	76	76	76
9	90	83	79	76	89	82	79	76	82	78	76	81	78	75	80	77	75	74	74	74
10	87	80	76	74	86	80	76	73	79	76	73	79	75	73	78	75	73	72	72	72

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	655286
5°	616991
10°	518291
15°	404148
20°	243963
25°	56535
30°	14798
35°	3508
40°	1159
45°	314
50°	192
55°	215
60°	247
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191540
 CATALOG NUMBER: LDA4A15930D010TE LAR35FL 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	448.8	27.9
10°-20°	845.3	52.6
20°-30°	289.3	18.0
30°-40°	20.6	1.3
40°-50°	2.0	0.1
50°-60°	0.9	0.1
60°-70°	0.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1583.5	98.5
0°-40°	1604.1	99.8
0°-60°	1606.9	100.0
0°-90°	1607.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1607.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5313	
5°	4983	449
15°	3165	845
25°	415	289
35°	23	21
45°	2	2
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191540

CATALOG NUMBER: LDA4A15930D010TE LAR35FL 4LA1

CANDELA DISTRIBUTION (FULL):

	0°
0°	5312.6
2.5°	5193.6
5°	4983.1
7.5°	4626.8
10°	4138.1
12.5°	3663.6
15°	3164.9
17.5°	2559.7
20°	1858.6
22.5°	1110.1
25°	415.4
27.5°	202.4
30°	103.9
32.5°	46.5
35°	23.3
37.5°	12.5
40°	7.2
42.5°	3.5
45°	1.8
47.5°	1.0
50°	1.0
52.5°	1.0
55°	1.0
57.5°	1.0
60°	1.0
62.5°	1.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)