

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191558

Luminaire Tested: **LDA4A15935D010TE LAR35FL 4LA1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191558
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25630)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A15935D010TE LAR35FL 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1619.7 lumens
Efficiency: N/A
Efficacy: 79.4 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191558

CATALOG NUMBER: LDA4A15935D010TE LAR35FL 4LA1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191558

CATALOG NUMBER: LDA4A15935D010TE LAR35FL 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	115	113	111	109	113	111	109	107	107	105	104	103	102	101	100	99	98	97		
2	111	108	104	102	109	106	103	101	103	101	99	100	98	97	97	96	95	93		
3	108	103	99	96	106	102	98	96	99	96	94	97	95	93	95	93	91	90		
4	104	99	95	92	103	98	94	91	96	93	90	94	91	89	92	90	88	87		
5	101	95	91	88	100	94	90	87	93	89	87	91	88	86	90	87	85	84		
6	98	92	87	84	97	91	87	84	90	86	84	88	85	83	87	85	83	81		
7	95	88	84	81	94	88	84	81	87	83	81	86	83	80	85	82	80	79		
8	92	86	81	78	91	85	81	78	84	81	78	83	80	78	82	80	77	76		
9	90	83	79	76	89	82	79	76	82	78	76	81	78	75	80	77	75	74		
10	87	80	76	74	86	80	76	73	79	76	73	79	75	73	78	75	73	72		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	660355
5°	621771
10°	522286
15°	407263
20°	245853
25°	56970
30°	14898
35°	3539
40°	1159
45°	314
50°	192
55°	215
60°	247
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191558
 CATALOG NUMBER: LDA4A15935D010TE LAR35FL 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	452.3	27.9
10°-20°	851.8	52.6
20°-30°	291.6	18.0
30°-40°	20.8	1.3
40°-50°	2.0	0.1
50°-60°	0.9	0.1
60°-70°	0.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1595.7	98.5
0°-40°	1616.5	99.8
0°-60°	1619.3	100.0
0°-90°	1619.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1619.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5354	
5°	5022	452
15°	3189	852
25°	419	292
35°	24	21
45°	2	2
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191558

CATALOG NUMBER: LDA4A15935D010TE LAR35FL 4LA1

CANDELA DISTRIBUTION (FULL):

	0°
0°	5353.7
2.5°	5233.7
5°	5021.7
7.5°	4662.6
10°	4170.0
12.5°	3691.8
15°	3189.3
17.5°	2579.5
20°	1873.0
22.5°	1118.7
25°	418.6
27.5°	203.9
30°	104.6
32.5°	46.9
35°	23.5
37.5°	12.7
40°	7.2
42.5°	3.5
45°	1.8
47.5°	1.0
50°	1.0
52.5°	1.0
55°	1.0
57.5°	1.0
60°	1.0
62.5°	1.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)