

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191648

Luminaire Tested: **LDA4A20935D010TE LAR35FL 4LA1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191648
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25630)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A20935D010TE LAR35FL 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2130.6 lumens
Efficiency: N/A
Efficacy: 74.0 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191648

CATALOG NUMBER: LDA4A20935D010TE LAR35FL 4LA1

Luminous Intensity Polar Plot





TEST NUMBER: P1191648

CATALOG NUMBER: LDA4A20935D010TE LAR35FL 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			0
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	113	111	109	113	111	109	107		107	105	104			103	102	101			100
2	111	108	104	102	109	106	103	101		103	101	99			100	98	97			97
3	108	103	99	96	106	102	98	96		99	96	94			97	95	93			95
4	104	99	95	92	103	98	94	91		96	93	90			94	91	89			92
5	101	95	91	88	100	94	90	87		93	89	87			91	88	86			90
6	98	92	87	84	97	91	87	84		90	86	84			88	85	83			87
7	95	88	84	81	94	88	84	81		87	83	81			86	83	80			85
8	92	86	81	78	91	85	81	78		84	81	78			83	80	78			82
9	90	83	79	76	89	82	79	76		82	78	76			81	78	75			80
10	87	80	76	74	86	80	76	73		79	76	73			79	75	73			78

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	868723
5°	817971
10°	687100
15°	535777
20°	323429
25°	74949
30°	19612
35°	4638
40°	1546
45°	401
50°	230
55°	258
60°	296
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191648

CATALOG NUMBER: LDA4A20935D010TE LAR35FL 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	595.0	27.9
10°-20°	1120.6	52.6
20°-30°	383.6	18.0
30°-40°	27.3	1.3
40°-50°	2.6	0.1
50°-60°	1.1	0.1
60°-70°	0.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2099.2	98.5
0°-40°	2126.5	99.8
0°-60°	2130.2	100.0
0°-90°	2130.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2130.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7043	
5°	6606	595
15°	4196	1121
25°	551	384
35°	31	27
45°	2	3
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191648

CATALOG NUMBER: LDA4A20935D010TE LAR35FL 4LA1

CANDELA DISTRIBUTION (FULL):

	0°
0°	7043.0
2.5°	6885.2
5°	6606.3
7.5°	6133.8
10°	5485.9
12.5°	4856.8
15°	4195.7
17.5°	3393.4
20°	2464.0
22.5°	1471.7
25°	550.7
27.5°	268.2
30°	137.7
32.5°	61.7
35°	30.8
37.5°	16.7
40°	9.6
42.5°	4.8
45°	2.3
47.5°	1.2
50°	1.2
52.5°	1.2
55°	1.2
57.5°	1.2
60°	1.2
62.5°	1.2
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)