

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191656

Luminaire Tested: **LDA4A20940D010TE LAR15SP 4LAL1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191656
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26144)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A20940D010TE LAR15SP 4LAL1
Description: PORTFOLIO 4" Lensed Adjustable, Self-flange Trim Ring, 15° Spot
Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2229.0 lumens
Efficiency: N/A
Efficacy: 77.4 lumens/watt
Spacing Criteria (0/90/45): 0.29 / 0.29 / 0.34
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 28.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191656

CATALOG NUMBER: LDA4A20940D010TE LAR15SP 4LAL1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191656

CATALOG NUMBER: LDA4A20940D010TE LAR15SP 4LAL1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	113	112	110	113	111	110	108		107	106	105			104	103	102			100
2	112	108	106	103	110	107	104	102		104	102	100			101	99	98			98
3	109	104	101	98	107	103	100	98		101	98	96			98	96	95			96
4	106	101	97	94	104	100	96	94		98	95	93			96	94	92			94
5	103	97	94	91	102	97	93	90		95	92	90			94	91	89			92
6	100	95	91	88	99	94	90	88		93	89	87			91	89	87			90
7	98	92	88	85	97	91	88	85		90	87	85			89	86	84			88
8	95	89	86	83	95	89	85	83		88	85	83			87	84	82			86
9	93	87	83	81	92	87	83	81		86	83	81			85	82	80			85
10	91	85	81	79	90	85	81	79		84	81	79			83	81	79			83

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1864344
5°	1457138
10°	795741
15°	434629
20°	244632
25°	62115
30°	11793
35°	4231
40°	2045
45°	1116
50°	249
55°	280
60°	321
65°	379
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191656

CATALOG NUMBER: LDA4A20940D010TE LAR15SP 4LAL1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	930.2	41.7
10°-20°	966.9	43.4
20°-30°	303.3	13.6
30°-40°	21.3	1.0
40°-50°	5.0	0.2
50°-60°	1.2	0.1
60°-70°	1.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2200.4	98.7
0°-40°	2221.8	99.7
0°-60°	2227.9	99.9
0°-90°	2229.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2229.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	15115	
5°	11768	930
15°	3404	967
25°	456	303
35°	28	21
45°	6	5
55°	1	1
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191656

CATALOG NUMBER: LDA4A20940D010TE LAR15SP 4LAL1

CANDELA DISTRIBUTION (FULL):

	0°
0°	15114.8
1°	14873.9
2°	14324.5
3°	13592.7
4°	12783.3
5°	11768.5
6°	10567.7
7°	9312.2
8°	8182.7
9°	7199.8
10°	6353.3
11°	5612.7
12°	4962.7
13°	4387.7
14°	3870.2
15°	3403.6
17.5°	2457.7
20°	1863.7
22.5°	1268.4
25°	456.4
27.5°	152.9
30°	82.8
32.5°	45.9
35°	28.1
37.5°	19.1
40°	12.7
42.5°	9.0
45°	6.4
47.5°	3.8
50°	1.3
52.5°	1.3
55°	1.3
57.5°	1.3
60°	1.3
62.5°	1.3
65°	1.3
67.5°	1.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P1191656

CATALOG NUMBER: LDA4A20940D010TE LAR15SP 4LAL1

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



85°	0.0
87.5°	0.0

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)