

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191705

Luminaire Tested: **LDA4A25927D010TE LAR35FL 4LFC1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191705
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26143)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A25927D010TE LAR35FL 4LFC1
Description: PORTFOLIO 4" Flat Cone, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2589.5 lumens
Efficiency: N/A
Efficacy: 83.8 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.56
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 30.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191705

CATALOG NUMBER: LDA4A25927D010TE LAR35FL 4LFC1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191705

CATALOG NUMBER: LDA4A25927D010TE LAR35FL 4LFC1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	115	113	111	109	113	111	109	107	107	105	104		103	102	101		96
2	111	107	104	102	109	106	103	101	103	100	99		100	98	96		93
3	107	103	99	96	106	101	98	95	99	96	94		97	94	92		90
4	104	99	94	91	102	97	94	91	95	92	90		94	91	89		87
5	101	95	91	87	99	94	90	87	92	89	86		91	88	86		84
6	98	91	87	84	96	91	87	84	89	86	83		88	85	83		81
7	95	88	84	81	94	87	83	81	86	83	80		85	82	80		78
8	92	85	81	78	91	85	81	78	84	80	78		83	80	77		76
9	89	82	78	75	88	82	78	75	81	78	75		80	77	75		74
10	87	80	76	73	86	79	76	73	79	75	73		78	75	72		71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	982904
5°	969671
10°	800588
15°	645456
20°	417688
25°	101964
30°	24497
35°	6159
40°	1932
45°	419
50°	230
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191705

CATALOG NUMBER: LDA4A25927D010TE LAR35FL 4LFC1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	693.7	26.8
10°-20°	1355.7	52.4
20°-30°	501.6	19.4
30°-40°	35.3	1.4
40°-50°	3.0	0.1
50°-60°	0.1	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2551.0	98.5
0°-40°	2586.4	99.9
0°-60°	2589.5	100.0
0°-90°	2589.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2589.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7969	
5°	7832	694
15°	5055	1356
25°	749	502
35°	41	35
45°	2	3
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191705

CATALOG NUMBER: LDA4A25927D010TE LAR35FL 4LFC1

CANDELA DISTRIBUTION (FULL):

	0°
0°	7968.7
1°	7921.7
2°	7896.5
3°	7945.8
4°	7957.8
5°	7831.5
6°	7606.6
7°	7292.8
8°	6975.3
9°	6661.3
10°	6392.0
11°	6102.1
12°	5846.0
13°	5591.1
14°	5332.4
15°	5054.6
17.5°	4222.4
20°	3182.1
22.5°	1968.7
25°	749.2
27.5°	307.8
30°	172.0
32.5°	81.7
35°	40.9
37.5°	21.7
40°	12.0
42.5°	6.0
45°	2.4
47.5°	1.2
50°	1.2
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191705

CATALOG NUMBER: LDA4A25927D010TE LAR35FL 4LFC1

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



85°	0.0
87.5°	0.0

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)