

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P170481

Luminaire Tested: **LDA4A28927D010TE LAR35FL 4LA1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P170481
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25630)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A28927D010TE LAR35FL 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1983.4 lumens
Efficiency: N/A
Efficacy: 44.6 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct


Input Watts (W): 44.49
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P170481

CATALOG NUMBER: LDA4A28927D010TE LAR35FL 4LA1

Luminous Intensity Polar Plot





TEST NUMBER: P170481

CATALOG NUMBER: LDA4A28927D010TE LAR35FL 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	113	111	109	107	107	105	104		103	102	101		100
2	111	108	104	102	109	106	103	101	103	101	99		100	98	97		97
3	108	103	99	96	106	102	98	96	99	96	94		97	95	93		95
4	104	99	95	92	103	98	94	91	96	93	90		94	91	89		92
5	101	95	91	88	100	94	90	87	93	89	87		91	88	86		90
6	98	92	87	84	97	91	87	84	90	86	84		88	85	83		87
7	95	88	84	81	94	88	84	81	87	83	81		86	83	80		85
8	92	86	81	78	91	85	81	78	84	81	78		83	80	78		82
9	90	83	79	76	89	82	79	76	82	78	76		81	78	75		80
10	87	80	76	74	86	80	76	73	79	76	73		79	75	73		78

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	808703
5°	761448
10°	639619
15°	498758
20°	301075
25°	69777
30°	18259
35°	4322
40°	1417
45°	384
50°	211
55°	237
60°	271
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P170481

CATALOG NUMBER: LDA4A28927D010TE LAR35FL 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	553.9	27.9
10°-20°	1043.2	52.6
20°-30°	357.1	18.0
30°-40°	25.4	1.3
40°-50°	2.4	0.1
50°-60°	1.0	0.0
60°-70°	0.4	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1954.2	98.5
0°-40°	1979.6	99.8
0°-60°	1983.0	100.0
0°-90°	1983.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1983.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6556	
5°	6150	554
15°	3906	1043
25°	513	357
35°	29	25
45°	2	2
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P170481

CATALOG NUMBER: LDA4A28927D010TE LAR35FL 4LA1

CANDELA DISTRIBUTION (FULL):

0°	
0°	6556.4
2.5°	6409.4
5°	6149.8
7.5°	5710.0
10°	5106.8
12.5°	4521.2
15°	3905.8
17.5°	3158.9
20°	2293.7
22.5°	1370.1
25°	512.7
27.5°	249.7
30°	128.2
32.5°	57.5
35°	28.7
37.5°	15.5
40°	8.8
42.5°	4.4
45°	2.2
47.5°	1.1
50°	1.1
52.5°	1.1
55°	1.1
57.5°	1.1
60°	1.1
62.5°	1.1
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)