

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191783

Luminaire Tested: **LDA4A30927D010TE LAR15SP 4LFC1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191783
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26141)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A30927D010TE LAR15SP 4LFC1
Description: PORTFOLIO 4" Flat Cone, Self-flange Trim Ring, 15° Spot Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2783.6 lumens
Efficiency: N/A
Efficacy: 70.7 lumens/watt
Spacing Criteria (0/90/45): 0.32 / 0.32 / 0.36
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191783

CATALOG NUMBER: LDA4A30927D010TE LAR15SP 4LFC1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191783

CATALOG NUMBER: LDA4A30927D010TE LAR15SP 4LFC1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	113	112	110	113	111	110	108		107	106	105		104	103	102		100	100	99
2	112	109	106	103	110	107	104	102		104	102	100		101	99	98		98	97	96
3	109	104	101	98	107	103	100	98		101	98	96		98	96	95		96	95	93
4	106	101	97	94	104	100	97	94		98	95	93		96	94	92		94	92	91
5	103	98	94	91	102	97	93	91		95	92	90		94	91	89		92	90	89
6	100	95	91	88	99	94	91	88		93	90	87		92	89	87		91	88	86
7	98	92	88	86	97	92	88	86		91	87	85		90	87	85		89	86	84
8	96	90	86	83	95	89	86	83		88	85	83		88	85	83		87	84	82
9	94	88	84	81	93	87	84	81		86	83	81		86	83	81		85	82	81
10	91	85	82	79	91	85	82	79		84	81	79		84	81	79		83	81	79

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2174929
5°	1838939
10°	1007774
15°	550118
20°	306444
25°	70798
30°	13702
35°	3945
40°	1401
45°	506
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191783

CATALOG NUMBER: LDA4A30927D010TE LAR15SP 4LFC1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1169.5	42.0
10°-20°	1223.6	44.0
20°-30°	366.9	13.2
30°-40°	21.2	0.8
40°-50°	2.5	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2759.9	99.1
0°-40°	2781.2	99.9
0°-60°	2783.6	100.0
0°-90°	2783.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2783.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	17633	
5°	14852	###
15°	4308	1224
25°	520	367
35°	26	21
45°	3	2
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191783

CATALOG NUMBER: LDA4A30927D010TE LAR15SP 4LFC1

CANDELA DISTRIBUTION (FULL):

	0°
0°	17632.8
1°	17459.3
2°	17145.9
3°	16726.2
4°	16000.5
5°	14852.1
6°	13431.2
7°	11884.9
8°	10447.9
9°	9134.8
10°	8046.2
11°	7103.3
12°	6265.3
13°	5540.9
14°	4892.3
15°	4308.0
17.5°	3130.4
20°	2334.6
22.5°	1539.0
25°	520.2
27.5°	180.7
30°	96.2
32.5°	48.1
35°	26.2
37.5°	14.5
40°	8.7
42.5°	4.4
45°	2.9
47.5°	1.5
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P1191783
CATALOG NUMBER: LDA4A30927D010TE LAR15SP 4LFC1

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



85°	0.0
87.5°	0.0

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)