

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191794

Luminaire Tested: **LDA4A30927D010TE LAR35FL 4LAL1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191794
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26146)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A30927D010TE LAR35FL 4LAL1
Description: PORTFOLIO 4" Lensed Adjustable, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2846.4 lumens
Efficiency: N/A
Efficacy: 72.2 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.55
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 39.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191794

CATALOG NUMBER: LDA4A30927D010TE LAR35FL 4LAL1

Luminous Intensity Polar Plot





TEST NUMBER: P1191794

CATALOG NUMBER: LDA4A30927D010TE LAR35FL 4LAL1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	113	111	109	113	111	109	107		107	105	104			103	102	101			100
2	111	107	104	102	109	106	103	100		102	100	98			100	98	96			97
3	107	103	99	96	105	101	98	95		99	96	94			96	94	92			94
4	104	98	94	91	102	97	93	91		95	92	90			93	91	89			92
5	101	94	90	87	99	94	90	87		92	89	86			90	88	85			89
6	97	91	87	83	96	90	86	83		89	85	83			88	85	82			86
7	94	88	83	80	93	87	83	80		86	82	80			85	82	79			84
8	92	85	80	77	91	84	80	77		83	80	77			82	79	77			82
9	89	82	78	75	88	82	77	75		81	77	74			80	77	74			79
10	86	79	75	72	86	79	75	72		78	75	72			78	74	72			77

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1120163
5°	1026813
10°	866005
15°	702217
20°	454743
25°	131116
30°	28642
35°	8116
40°	3059
45°	1273
50°	556
55°	323
60°	370
65°	438
70°	541
75°	0
80°	0
85°	0



TEST NUMBER: P1191794

CATALOG NUMBER: LDA4A30927D010TE LAR35FL 4LAL1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	747.2	26.3
10°-20°	1475.4	51.8
20°-30°	568.4	20.0
30°-40°	45.0	1.6
40°-50°	6.5	0.2
50°-60°	1.5	0.1
60°-70°	1.5	0.1
70°-80°	0.6	0.0
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2791.0	98.1
0°-40°	2836.0	99.6
0°-60°	2843.9	99.9
0°-90°	2846.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2846.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9082	
5°	8293	747
15°	5499	1475
25°	963	568
35°	54	45
45°	7	6
55°	2	1
65°	2	1
75°	0	1
85°	0	1
90°	0	



TEST NUMBER: P1191794

CATALOG NUMBER: LDA4A30927D010TE LAR35FL 4LAL1

CANDELA DISTRIBUTION (FULL):

	0°
0°	9081.5
1°	9008.7
2°	8934.3
3°	8759.4
4°	8529.1
5°	8293.0
6°	8033.6
7°	7781.5
8°	7503.1
9°	7201.4
10°	6914.3
11°	6640.3
12°	6354.6
13°	6082.1
14°	5803.6
15°	5499.1
17.5°	4604.1
20°	3464.4
22.5°	2141.0
25°	963.4
27.5°	370.2
30°	201.1
32.5°	103.5
35°	53.9
37.5°	32.1
40°	19.0
42.5°	11.6
45°	7.3
47.5°	4.4
50°	2.9
52.5°	1.5
55°	1.5
57.5°	1.5
60°	1.5
62.5°	1.5
65°	1.5
67.5°	1.5
70°	1.5
72.5°	0.0
75°	0.0
77.5°	1.5
80°	0.0
82.5°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191794

CATALOG NUMBER: LDA4A30927D010TE LAR35FL 4LAL1

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



85°	0.0
87.5°	1.5

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)