

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P1191882

Luminaire Tested: **LDA4A35927D010TE LAR35FL 4LA1**

Issue Date: 3/3/2020

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

**Test Information**

Test Method: LM-41-14
Report Number: P1191882
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P25630)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA4A35927D010TE LAR35FL 4LA1
Description: PORTFOLIO 4" Adjustable Reflector, Self-flange Trim Ring, 35° Flood Optic, at 0° tilt
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2988.9 lumens
Efficiency: N/A
Efficacy: 63.5 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.54
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P1191882

CATALOG NUMBER: LDA4A35927D010TE LAR35FL 4LA1

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P1191882

CATALOG NUMBER: LDA4A35927D010TE LAR35FL 4LA1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	113	111	109	113	111	109	107		107	105	104		103	102	101		100	99	98
2	111	108	104	102	109	106	103	101		103	101	99		100	98	97		97	96	95
3	108	103	99	96	106	102	98	96		99	96	94		97	95	93		95	93	91
4	104	99	95	92	103	98	94	91		96	93	90		94	91	89		92	90	88
5	101	95	91	88	100	94	90	87		93	89	87		91	88	86		90	87	85
6	98	92	87	84	97	91	87	84		90	86	84		88	85	83		87	85	83
7	95	88	84	81	94	88	84	81		87	83	81		86	83	80		85	82	80
8	92	86	81	78	91	85	81	78		84	81	78		83	80	78		82	80	77
9	90	83	79	76	89	82	79	76		82	78	76		81	78	75		80	77	75
10	87	80	76	74	86	80	76	73		79	76	73		79	75	73		78	75	73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1218667
5°	1147460
10°	963862
15°	751598
20°	453706
25°	105148
30°	27517
35°	6505
40°	2142
45°	576
50°	326
55°	366
60°	419
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P1191882
 CATALOG NUMBER: LDA4A35927D010TE LAR35FL 4LA1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	834.7	27.9
10°-20°	1572.0	52.6
20°-30°	538.1	18.0
30°-40°	38.3	1.3
40°-50°	3.6	0.1
50°-60°	1.5	0.1
60°-70°	0.6	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2944.8	98.5
0°-40°	2983.1	99.8
0°-60°	2988.2	100.0
0°-90°	2988.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2988.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9880	
5°	9267	835
15°	5886	1572
25°	773	538
35°	43	38
45°	3	4
55°	2	2
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P1191882

CATALOG NUMBER: LDA4A35927D010TE LAR35FL 4LA1

CANDELA DISTRIBUTION (FULL):

	0°
0°	9880.1
2.5°	9658.6
5°	9267.4
7.5°	8604.6
10°	7695.6
12.5°	6813.2
15°	5885.8
17.5°	4760.3
20°	3456.5
22.5°	2064.7
25°	772.6
27.5°	376.3
30°	193.2
32.5°	86.6
35°	43.2
37.5°	23.4
40°	13.3
42.5°	6.6
45°	3.3
47.5°	1.7
50°	1.7
52.5°	1.7
55°	1.7
57.5°	1.7
60°	1.7
62.5°	1.7
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)