

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211190

Luminaire Tested: **LE_4B15D010 EC4B10208030 4LBN1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211190
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B15D010 EC4B10208030 4LBN1H
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1083.9 lumens
Efficiency: N/A
Efficacy: 75.8 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211190

CATALOG NUMBER: LE_4B15D010 EC4B10208030 4LBN1H

Luminous Intensity Polar Plot





TEST NUMBER: P211190

CATALOG NUMBER: LE_4B15D010 EC4B10208030 4LBN1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	77	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211190

CATALOG NUMBER: LE_4B15D010 EC4B10208030 4LBN1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	122.8	11.3
10°-20°	297.8	27.5
20°-30°	345.8	31.9
30°-40°	229.0	21.1
40°-50°	64.2	5.9
50°-60°	16.1	1.5
60°-70°	6.1	0.6
70°-80°	2.1	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	766.4	70.7
0°-40°	995.4	91.8
0°-60°	1075.7	99.2
0°-90°	1083.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1083.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1361	
5°	1325	123
15°	1066	298
25°	758	346
35°	367	229
45°	75	64
55°	18	16
65°	6	6
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P211190

CATALOG NUMBER: LE_4B15D010 EC4B10208030 4LBN1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1360.8
2.5°	1354.9
5°	1325.4
7.5°	1274.4
10°	1211.6
12.5°	1140.9
15°	1066.3
17.5°	993.7
20°	913.2
22.5°	838.4
25°	757.9
27.5°	681.4
30°	583.2
32.5°	479.1
35°	367.3
37.5°	263.1
40°	178.6
42.5°	115.9
45°	74.6
47.5°	45.1
50°	29.5
52.5°	21.6
55°	17.6
57.5°	13.7
60°	9.9
62.5°	7.9
65°	5.9
67.5°	3.9
70°	3.9
72.5°	2.0
75°	2.0
77.5°	2.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)