

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211232

Luminaire Tested: **LE_4B15D010 EC4B10209030 4LBW1GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211232
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B15D010 EC4B10209030 4LBW1GPH
Description: PORTFOLIO 4 INCH CYLINDER
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 969.6 lumens
Efficiency: N/A
Efficacy: 67.8 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211232

CATALOG NUMBER: LE_4B15D010 EC4B10209030 4LBW1GPH

Luminous Intensity Polar Plot






TEST NUMBER: P211232

CATALOG NUMBER: LE_4B15D010 EC4B10209030 4LBW1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	99		100	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	78	74	92	84	78	73	81	76	72		79	75	71		77
5	88	78	72	67	86	77	71	66	75	70	66		74	69	65		72
6	83	72	65	61	81	71	65	60	70	64	60		68	63	59		67
7	78	67	60	55	76	66	60	55	65	59	55		64	58	55		63
8	73	62	56	51	72	62	55	51	61	55	51		59	54	50		58
9	69	58	51	47	68	58	51	47	57	51	47		56	50	46		55
10	65	54	48	43	64	54	48	43	53	47	43		52	47	43		51

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211232

CATALOG NUMBER: LE_4B15D010 EC4B10209030 4LBW1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.8	6.8
10°-20°	186.6	19.2
20°-30°	267.6	27.6
30°-40°	251.9	26.0
40°-50°	139.1	14.3
50°-60°	44.6	4.6
60°-70°	11.1	1.1
70°-80°	2.6	0.3
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	520.0	53.6
0°-40°	771.9	79.6
0°-60°	955.7	98.6
0°-90°	969.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	969.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	698	
5°	695	66
15°	661	187
25°	587	268
35°	409	252
45°	177	139
55°	45	45
65°	10	11
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P211232

CATALOG NUMBER: LE_4B15D010 EC4B10209030 4LBW1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	697.9
2.5°	692.9
5°	694.6
7.5°	689.5
10°	681.2
12.5°	672.7
15°	661.0
17.5°	650.9
20°	634.1
22.5°	610.5
25°	587.0
27.5°	554.9
30°	513.0
32.5°	465.9
35°	408.7
37.5°	348.1
40°	285.9
42.5°	228.8
45°	176.6
47.5°	132.8
50°	95.8
52.5°	67.3
55°	45.4
57.5°	30.3
60°	21.8
62.5°	15.1
65°	10.1
67.5°	6.7
70°	5.0
72.5°	3.4
75°	1.6
77.5°	1.6
80°	1.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)