

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211284

Luminaire Tested: **LE_4B15D010 EC4B10208035 4LBS1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211284
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B15D010 EC4B10208035 4LBS1H
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1745.9 lumens
Efficiency: N/A
Efficacy: 122.1 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211284

CATALOG NUMBER: LE_4B15D010 EC4B10208035 4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P211284

CATALOG NUMBER: LE_4B15D010 EC4B10208035 4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88		
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77		
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67		
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58		
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51		
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46		
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41		
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37		
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34		
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211284

CATALOG NUMBER: LE_4B15D010 EC4B10208035 4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	85.5	4.9
10°-20°	232.5	13.3
20°-30°	322.9	18.5
30°-40°	352.3	20.2
40°-50°	328.7	18.8
50°-60°	249.4	14.3
60°-70°	136.6	7.8
70°-80°	37.6	2.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	640.9	36.7
0°-40°	993.2	56.9
0°-60°	1571.2	90.0
0°-90°	1745.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1745.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	913	
5°	906	86
15°	829	232
25°	702	323
35°	563	352
45°	427	329
55°	279	249
65°	136	137
75°	33	38
85°	0	1
90°	0	



TEST NUMBER: P211284

CATALOG NUMBER: LE_4B15D010 EC4B10208035 4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	913.2
2.5°	913.2
5°	905.5
7.5°	893.9
10°	876.6
12.5°	853.5
15°	828.6
17.5°	797.8
20°	769.0
22.5°	734.4
25°	701.7
27.5°	669.0
30°	632.4
32.5°	597.9
35°	563.3
37.5°	528.6
40°	496.0
42.5°	461.3
45°	426.8
47.5°	392.2
50°	353.7
52.5°	317.1
55°	278.7
57.5°	242.2
60°	205.7
62.5°	169.1
65°	136.5
67.5°	105.7
70°	78.8
72.5°	53.8
75°	32.7
77.5°	15.4
80°	3.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)