

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211673

Luminaire Tested: **LE_4B20D010 EC4B10209035 4LBCS1MMS**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P211673
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LE_4B20D010 EC4B10209035 4LBCS1MMS
Description: PORTFOLIO 4 INCH CYLINDER
SHALLOW DISTRIBUTION WITH CAST MATTE BLACK TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1794.4 lumens
Efficiency: N/A
Efficacy: 86.3 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P211673

CATALOG NUMBER: LE_4B20D010 EC4B10209035 4LBCS1MMS

Luminous Intensity Polar Plot






TEST NUMBER: P211673

CATALOG NUMBER: LE_4B20D010 EC4B10209035 4LBCS1MMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88		
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76		
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65		
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57		
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50		
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44		
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40		
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36		
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32		
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P211673

CATALOG NUMBER: LE_4B20D010 EC4B10209035 4LBCS1MMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	77.7	4.3
10°-20°	217.9	12.1
20°-30°	318.3	17.7
30°-40°	364.0	20.3
40°-50°	349.8	19.5
50°-60°	270.1	15.1
60°-70°	150.8	8.4
70°-80°	43.9	2.4
80°-90°	1.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	613.8	34.2
0°-40°	977.8	54.5
0°-60°	1597.8	89.0
0°-90°	1794.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1794.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	824	
5°	817	78
15°	773	218
25°	692	318
35°	583	364
45°	456	350
55°	303	270
65°	151	151
75°	38	44
85°	1	2
90°	0	



TEST NUMBER: P211673

CATALOG NUMBER: LE_4B20D010 EC4B10209035 4LBCS1MMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	824.1
2.5°	824.1
5°	817.1
7.5°	813.6
10°	801.9
12.5°	788.0
15°	772.9
17.5°	757.8
20°	735.8
22.5°	718.4
25°	691.7
27.5°	665.0
30°	638.3
32.5°	611.7
35°	582.7
37.5°	553.6
40°	519.9
42.5°	489.8
45°	456.1
47.5°	417.8
50°	381.9
52.5°	342.3
55°	302.9
57.5°	262.3
60°	224.0
62.5°	185.7
65°	150.9
67.5°	118.4
70°	88.2
72.5°	61.5
75°	38.3
77.5°	19.7
80°	7.0
82.5°	2.3
85°	1.2
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)