

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P210724

Luminaire Tested: **LSR4B10D010BZ EC4B10208027 4LB NB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P210724
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR4B10D010BZ EC4B10208027 4LBNB1
Description: PORTFOLIO 4 INCH CYLINDER
NARROW DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 398.4 lumens
Efficiency: N/A
Efficacy: 40.2 lumens/watt
Spacing Criteria (0/90/45): 0.62 / 0.62 / 0.79
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P210724

CATALOG NUMBER: LSR4B10D010BZ EC4B10208027 4LBNB1

Luminous Intensity Polar Plot






TEST NUMBER: P210724

CATALOG NUMBER: LSR4B10D010BZ EC4B10208027 4LBNB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98
2	109	104	100	97	106	102	99	96	99	96	94		96	94	92		93
3	104	98	93	89	102	96	92	88	94	90	87		91	88	86		89
4	99	92	86	82	97	90	86	82	88	84	81		86	83	80		85
5	94	86	81	77	92	85	80	76	84	79	76		82	78	75		80
6	90	81	76	72	88	81	75	71	79	74	71		78	74	70		76
7	86	77	71	67	84	76	71	67	75	70	67		74	69	66		73
8	82	73	67	63	80	72	67	63	71	66	63		70	66	62		69
9	78	69	63	60	77	68	63	59	67	63	59		67	62	59		66
10	75	65	60	56	74	65	60	56	64	59	56		63	59	56		63

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P210724

CATALOG NUMBER: LSR4B10D010BZ EC4B10208027 4LBNB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.3	13.6
10°-20°	115.1	28.9
20°-30°	133.6	33.5
30°-40°	83.6	21.0
40°-50°	11.8	3.0
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	303.0	76.1
0°-40°	386.7	97.0
0°-60°	398.4	100.0
0°-90°	398.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	398.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	652	
5°	604	54
15°	409	115
25°	295	134
35°	134	84
45°	10	12
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P210724

CATALOG NUMBER: LSR4B10D010BZ EC4B10208027 4LBNB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	651.5
2.5°	638.7
5°	603.7
7.5°	553.6
10°	502.3
12.5°	453.4
15°	409.1
17.5°	371.8
20°	343.8
22.5°	318.2
25°	294.9
27.5°	266.9
30°	230.8
32.5°	185.3
35°	134.0
37.5°	87.4
40°	50.1
42.5°	25.6
45°	10.5
47.5°	2.3
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)