

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P211129

Luminaire Tested: **LSR4B15D010BZ EC4B10209027 4LBMWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P211129  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSR4B15D010BZ EC4B10209027 4LBMWH1  
Description: PORTFOLIO 4 INCH CYLINDER  
MEDIUM DISTRIBUTION WITH WHEAT TRIM  
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W  
DL3-15.28W DLE-15.432W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 943.2 lumens  
Efficiency: N/A  
Efficacy: 66.0 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.87  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 14.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P211129

CATALOG NUMBER: LSR4B15D010BZ EC4B10209027 4LBMWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P211129

CATALOG NUMBER: LSR4B15D010BZ EC4B10209027 4LBMWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| RF  | 20  |     |     |     |  | 20  |     |     |     |  | 20  |     |     |  |     | 20  |     |  |     |     | 20  |
| RC  | 80  |     |     |     |  | 70  |     |     |     |  | 50  |     |     |  |     | 30  |     |  |     |     | 10  |
| RW  | 70  | 50  | 30  | 10  |  | 70  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |
| RCR |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
| 0   | 119 | 119 | 119 | 119 |  | 116 | 116 | 116 | 116 |  | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 |
| 1   | 114 | 111 | 108 | 106 |  | 111 | 109 | 106 | 105 |  | 105 | 103 | 101 |  | 101 | 100 | 98  |  | 98  | 96  | 95  |
| 2   | 108 | 103 | 99  | 96  |  | 106 | 102 | 98  | 95  |  | 98  | 95  | 93  |  | 95  | 93  | 91  |  | 93  | 91  | 89  |
| 3   | 103 | 96  | 91  | 88  |  | 101 | 95  | 90  | 87  |  | 92  | 89  | 85  |  | 90  | 87  | 84  |  | 88  | 85  | 83  |
| 4   | 98  | 90  | 85  | 81  |  | 96  | 89  | 84  | 80  |  | 87  | 83  | 79  |  | 85  | 81  | 78  |  | 83  | 80  | 77  |
| 5   | 93  | 84  | 79  | 74  |  | 91  | 84  | 78  | 74  |  | 82  | 77  | 73  |  | 80  | 76  | 73  |  | 79  | 75  | 72  |
| 6   | 88  | 79  | 73  | 69  |  | 87  | 79  | 73  | 69  |  | 77  | 72  | 68  |  | 76  | 71  | 68  |  | 74  | 71  | 68  |
| 7   | 84  | 75  | 69  | 65  |  | 82  | 74  | 68  | 64  |  | 73  | 68  | 64  |  | 72  | 67  | 64  |  | 70  | 66  | 63  |
| 8   | 80  | 70  | 64  | 60  |  | 79  | 70  | 64  | 60  |  | 69  | 64  | 60  |  | 68  | 63  | 60  |  | 67  | 63  | 59  |
| 9   | 76  | 66  | 61  | 57  |  | 75  | 66  | 60  | 57  |  | 65  | 60  | 56  |  | 64  | 60  | 56  |  | 63  | 59  | 56  |
| 10  | 73  | 63  | 57  | 53  |  | 72  | 62  | 57  | 53  |  | 62  | 57  | 53  |  | 61  | 56  | 53  |  | 60  | 56  | 53  |

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P211129

CATALOG NUMBER: LSR4B15D010BZ EC4B10209027 4LBMWH1

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 103.5  | 11.0      |
| 10°-20°   | 266.1  | 28.2      |
| 20°-30°   | 312.2  | 33.1      |
| 30°-40°   | 197.5  | 20.9      |
| 40°-50°   | 52.9   | 5.6       |
| 50°-60°   | 7.4    | 0.8       |
| 60°-70°   | 2.8    | 0.3       |
| 70°-80°   | 0.9    | 0.1       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| <hr/>     |        |           |
| 0°-30°    | 681.7  | 72.3      |
| 0°-40°    | 879.2  | 93.2      |
| 0°-60°    | 939.6  | 99.6      |
| 0°-90°    | 943.2  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 943.2  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1120 |      |
| 5°  | 1102 | 103  |
| 15° | 953  | 266  |
| 25° | 690  | 312  |
| 35° | 314  | 198  |
| 45° | 60   | 53   |
| 55° | 7    | 7    |
| 65° | 3    | 3    |
| 75° | 1    | 1    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P211129

CATALOG NUMBER: LSR4B15D010BZ EC4B10209027 4LBMWH1

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 1120.2 |
| 2.5°  | 1116.0 |
| 5°    | 1102.1 |
| 7.5°  | 1079.8 |
| 10°   | 1047.8 |
| 12.5° | 1006.0 |
| 15°   | 953.0  |
| 17.5° | 898.7  |
| 20°   | 833.2  |
| 22.5° | 766.3  |
| 25°   | 689.7  |
| 27.5° | 606.1  |
| 30°   | 512.7  |
| 32.5° | 411.0  |
| 35°   | 313.5  |
| 37.5° | 227.1  |
| 40°   | 156.0  |
| 42.5° | 100.3  |
| 45°   | 59.9   |
| 47.5° | 33.4   |
| 50°   | 18.1   |
| 52.5° | 9.8    |
| 55°   | 7.0    |
| 57.5° | 5.6    |
| 60°   | 4.2    |
| 62.5° | 4.2    |
| 65°   | 2.8    |
| 67.5° | 1.4    |
| 70°   | 1.4    |
| 72.5° | 1.4    |
| 75°   | 1.4    |
| 77.5° | 0.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |
| 85°   | 0.0    |
| 87.5° | 0.0    |
| 90°   | 0.0    |



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)