

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P432456

Luminaire Tested: **LAM4B208R259024DE010x1MW**

Issue Date: 11/23/2020

Test Information

Test Method: LM-41-14
Report Number: P432456
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1911-585-5)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 11/23/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LAM4B208R259024DE010x1MW
Description: PORTFOLIO 4INCH ADJUSTABLE MULTIPLE, 25 DEG TIR OPTIC
Light Source: HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1428.0 lumens
Efficiency: N/A
Efficacy: 69.3 lumens/watt
Spacing Criteria (0/90/45): 0.45 / 0.45 / 0.41
Luminous Opening: Circular (Dia: 0.29' x H: 0')
CIE Type: Direct


Input Watts (W): 20.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P432456

CATALOG NUMBER: LAM4B208R259024DE010x1MW

Luminous Intensity Polar Plot



TEST NUMBER: P432456

CATALOG NUMBER: LAM4B208R259024DE010x1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	115	113	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97						
2	112	109	106	103	110	107	104	102	104	102	100	101	99	98	98	97	96	95						
3	109	104	101	99	107	103	100	98	101	98	96	99	96	95	96	95	93	92						
4	106	101	97	95	104	100	97	94	98	95	93	96	94	92	94	93	91	90						
5	103	98	94	91	102	97	93	91	95	92	90	94	91	89	92	90	89	88						
6	100	95	91	88	99	94	91	88	93	90	87	92	89	87	91	88	86	85						
7	98	92	88	86	97	92	88	86	91	87	85	90	87	85	89	86	84	83						
8	96	90	86	83	95	89	86	83	88	85	83	88	85	83	87	84	82	81						
9	94	88	84	81	93	87	84	81	86	83	81	86	83	81	85	82	81	80						
10	91	85	82	79	91	85	82	79	84	81	79	84	81	79	83	81	79	78						

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1123844
5°	1047940
10°	829806
15°	417618
20°	134017
25°	46857
30°	15701
35°	3147
40°	1030
45°	0
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P432456

CATALOG NUMBER: LAM4B208R259024DE010x1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	573.7	40.2
10°-20°	695.9	48.7
20°-30°	141.6	9.9
30°-40°	16.0	1.1
40°-50°	0.8	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1411.1	98.8
0°-40°	1427.2	99.9
0°-60°	1428.0	100.0
0°-90°	1428.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1428.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6976	
5°	6480	574
15°	2504	696
25°	264	142
35°	16	16
45°	0	1
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P432456

CATALOG NUMBER: LAM4B208R259024DE010x1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	6975.9
2.5°	6841.0
5°	6480.0
7.5°	5884.4
10°	5072.5
12.5°	3909.6
15°	2503.9
17.5°	1410.6
20°	781.7
22.5°	445.3
25°	263.6
27.5°	157.7
30°	84.4
32.5°	37.0
35°	16.0
37.5°	9.9
40°	4.9
42.5°	1.8
45°	0.0
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)