

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P433923

Luminaire Tested: **LAMR4B208R709027DE010x1MW**

Issue Date: 11/23/2020

Test Information

Test Method: LM-41-14
Report Number: P433923
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2007-857-14)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 11/23/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LAMR4B208R709027DE010x1MW
Description: PORTFOLIO 4INCH ADJUSTABLE MULTIPLE, 70 DEG TIR OPTIC
Light Source: HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1488.6 lumens
Efficiency: N/A
Efficacy: 72.3 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.09
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P433923

CATALOG NUMBER: LAMR4B208R709027DE010x1MW

Luminous Intensity Polar Plot





TEST NUMBER: P433923

CATALOG NUMBER: LAMR4B208R709027DE010x1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	100		100	98	97		96
2	106	101	96	92	104	99	95	91	96	92	89		93	90	87		90
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78
5	88	79	72	68	87	78	72	67	76	71	67		74	70	66		73
6	83	73	66	62	82	72	66	61	71	65	61		69	64	60		68
7	78	68	61	56	77	67	61	56	66	60	56		65	59	56		63
8	74	63	57	52	73	63	56	52	62	56	52		60	55	51		59
9	70	59	52	48	69	59	52	48	58	52	48		57	51	48		56
10	66	55	49	45	65	55	49	44	54	48	44		53	48	44		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	539856
5°	529784
10°	535910
15°	551085
20°	552031
25°	500833
30°	447504
35°	393004
40°	289377
45°	162086
50°	79750
55°	44729
60°	27136
65°	17862
70°	13271
75°	11628
80°	8808
85°	8491



TEST NUMBER: P433923

CATALOG NUMBER: LAMR4B208R709027DE010x1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	102.3	6.9
10°-20°	304.0	20.4
20°-30°	421.9	28.3
30°-40°	396.9	26.7
40°-50°	189.5	12.7
50°-60°	50.1	3.4
60°-70°	15.8	1.1
70°-80°	6.4	0.4
80°-90°	1.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	828.2	55.6
0°-40°	1225.1	82.3
0°-60°	1464.7	98.4
0°-90°	1488.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1488.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1094	
5°	1070	102
15°	1079	304
25°	920	422
35°	652	397
45°	232	189
55°	52	50
65°	15	16
75°	6	6
85°	2	2
90°	0	



TEST NUMBER: P433923

CATALOG NUMBER: LAMR4B208R709027DE010x1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	1094.2
2.5°	1080.4
5°	1069.7
7.5°	1068.2
10°	1069.7
12.5°	1072.8
15°	1078.9
17.5°	1078.9
20°	1051.4
22.5°	993.3
25°	920.0
27.5°	846.6
30°	785.5
32.5°	725.9
35°	652.5
37.5°	557.8
40°	449.3
42.5°	334.7
45°	232.3
47.5°	154.3
50°	103.9
52.5°	71.8
55°	52.0
57.5°	36.7
60°	27.5
62.5°	19.9
65°	15.3
67.5°	10.7
70°	9.2
72.5°	7.6
75°	6.1
77.5°	4.6
80°	3.1
82.5°	3.1
85°	1.5
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)