

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P761727

Luminaire Tested: LD6D15D010-EU6DR650215IC9030-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P761727
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D15D010-EU6DR650215IC9030-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1223.7 lumens
Efficiency: N/A
Efficacy: 77.4 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P761727

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P761727

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	89	84	79	95	88	83	79	86	82	78		84	80	77		82
5	92	83	78	73	90	83	77	73	81	76	72		79	75	72		77
6	87	78	72	68	86	77	72	68	76	71	67		74	70	67		73
7	83	73	67	63	81	73	67	63	71	66	62		70	66	62		69
8	79	69	63	59	77	68	63	59	67	62	58		66	62	58		65
9	75	65	59	55	74	65	59	55	64	58	55		63	58	55		62
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	131648
5°	131745
10°	136386
15°	136620
20°	125772
25°	107174
30°	82044
35°	57955
40°	34217
45°	13891
50°	5031
55°	2800
60°	1595
65°	879
70°	926
75°	718
80°	755
85°	627

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 13891 cd/sqm



TEST NUMBER: P761727

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	116.0	9.5
10°-20°	334.7	27.3
20°-30°	401.5	32.8
30°-40°	269.8	22.1
40°-50°	80.8	6.6
50°-60°	14.2	1.2
60°-70°	4.0	0.3
70°-80°	2.0	0.2
80°-90°	0.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	852.2	69.6
0°-40°	1122.0	91.7
0°-60°	1217.1	99.5
0°-90°	1223.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1223.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1205	
5°	1201	116
15°	1208	335
25°	889	402
35°	434	270
45°	90	81
55°	15	14
65°	3	4
75°	2	2
85°	0	1
90°	0	



TEST NUMBER: P761727

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1204.9
2.5°	1210.0
5°	1201.2
7.5°	1219.4
10°	1229.3
12.5°	1227.0
15°	1207.8
17.5°	1160.9
20°	1081.7
22.5°	988.6
25°	889.0
27.5°	776.5
30°	650.3
32.5°	535.9
35°	434.5
37.5°	334.4
40°	239.9
42.5°	156.6
45°	89.9
47.5°	47.6
50°	29.6
52.5°	20.6
55°	14.7
57.5°	10.6
60°	7.3
62.5°	4.8
65°	3.4
67.5°	3.1
70°	2.9
72.5°	2.2
75°	1.7
77.5°	1.5
80°	1.2
82.5°	0.9
85°	0.5
87.5°	0.3
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)