

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P761731

Luminaire Tested: LD6D15D010-EU6DR650215IC9030-6LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P761731
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D15D010-EU6DR650215IC9030-6LBS1H
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1288.1 lumens
Efficiency: N/A
Efficacy: 81.5 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P761731

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P761731

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	68309
5°	68136
10°	68082
15°	65978
20°	60070
25°	52346
30°	43532
35°	34494
40°	24900
45°	15726
50°	8196
55°	4358
60°	2289
65°	1258
70°	529
75°	587
80°	404
85°	335

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 15726 cd/sqm



TEST NUMBER: P761731

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	110.6	8.6
10°-20°	302.9	23.5
20°-30°	370.2	28.7
30°-40°	300.4	23.3
40°-50°	149.7	11.6
50°-60°	41.8	3.2
60°-70°	9.5	0.7
70°-80°	2.5	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	783.7	60.8
0°-40°	1084.1	84.2
0°-60°	1275.5	99.0
0°-90°	1288.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1288.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1170	
5°	1162	111
15°	1091	303
25°	812	370
35°	484	300
45°	190	150
55°	43	42
65°	9	9
75°	3	2
85°	0	1
90°	0	



TEST NUMBER: P761731

CATALOG NUMBER: LD6D15D010-EU6DR650215IC9030-6LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1169.6
2.5°	1168.8
5°	1162.2
7.5°	1158.4
10°	1148.0
12.5°	1126.7
15°	1091.2
17.5°	1035.9
20°	966.5
22.5°	891.5
25°	812.3
27.5°	727.5
30°	645.5
32.5°	564.6
35°	483.8
37.5°	403.2
40°	326.6
42.5°	254.7
45°	190.4
47.5°	132.7
50°	90.2
52.5°	62.2
55°	42.8
57.5°	28.9
60°	19.6
62.5°	13.6
65°	9.1
67.5°	4.6
70°	3.1
72.5°	2.9
75°	2.6
77.5°	1.7
80°	1.2
82.5°	0.9
85°	0.5
87.5°	0.3
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)