

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P761813

Luminaire Tested: LD6D15D010-EU6DR700215IC9035-6LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P761813
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D15D010-EU6DR700215IC9035-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1488.2 lumens
Efficiency: N/A
Efficacy: 94.2 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P761813

CATALOG NUMBER: LD6D15D010-EU6DR700215IC9035-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P761813

CATALOG NUMBER: LD6D15D010-EU6DR700215IC9035-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	182815
5°	177382
10°	172433
15°	170182
20°	158910
25°	119374
30°	84391
35°	29891
40°	15718
45°	16734
50°	17338
55°	17658
60°	17766
65°	17399
70°	16420
75°	15197
80°	13528
85°	11032

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 57.5°

Luminance: 17773 cd/sqm



TEST NUMBER: P761813

CATALOG NUMBER: LD6D15D010-EU6DR700215IC9035-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	152.5	10.3
10°-20°	418.4	28.1
20°-30°	460.8	31.0
30°-40°	176.1	11.8
40°-50°	83.1	5.6
50°-60°	82.6	5.6
60°-70°	66.2	4.4
70°-80°	38.0	2.6
80°-90°	10.3	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1031.8	69.3
0°-40°	1207.9	81.2
0°-60°	1373.6	92.3
0°-90°	1488.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1488.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1673	
5°	1617	153
15°	1504	418
25°	990	461
35°	224	176
45°	108	83
55°	93	83
65°	67	66
75°	36	38
85°	9	10
90°	0	



TEST NUMBER: P761813

CATALOG NUMBER: LD6D15D010-EU6DR700215IC9035-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1673.2
2.5°	1655.7
5°	1617.3
7.5°	1585.2
10°	1554.2
12.5°	1528.0
15°	1504.5
17.5°	1447.4
20°	1366.7
22.5°	1192.4
25°	990.2
27.5°	862.0
30°	668.9
32.5°	432.1
35°	224.1
37.5°	121.1
40°	110.2
42.5°	109.4
45°	108.3
47.5°	105.9
50°	102.0
52.5°	97.5
55°	92.7
57.5°	87.4
60°	81.3
62.5°	74.4
65°	67.3
67.5°	59.4
70°	51.4
72.5°	43.4
75°	36.0
77.5°	28.4
80°	21.5
82.5°	15.1
85°	8.8
87.5°	3.4
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)